



## Husqvarna 125BVx

An efficient hand held garden blower that combines high blowing power with user friendliness. Well balanced and easy to manoeuvre thanks to the in-line air outlet. Easy to start with Smart Start® technology. Delivered with flat and round nozzle. Vac kit included.



### Easy starting

Air purge for very easy starting.




### Multi-Speed Control

Variable speed throttle with cruise control option for easier handling

### Simple Starting

When the stop switch has been used, it is automatically reset to ON to facilitate the next start.



### Adjustable Tube Length

Easily adjust the blowing tube length for maximum performance



## FEATURES

- When the stop switch has been used, it is automatically reset to ON to facilitate the next start.
- Variable speed throttle with cruise control option for easier handling
- Air purge removes air from carburetor and fuel system for easy starting
- Easily adjust the blowing tube length for maximum performance
- 470 CFM for maximum blowing performance
- Balanced for less strain on your arms, shoulders and back
- Turn the blower into a mulching lawn vacuum to easily break down and collect debris

Technical Specifications	
<b>CAPACITY</b>	
Air flow in housing	13.31 m <sup>3</sup> /min
Air flow in pipe	12.03 m <sup>3</sup> /min
Air speed	76 m/s
Air speed (flat nozzle)	76 m/s
Air speed (round nozzle)	58.12 m/s
Blow speed	273 km/h
Blowing Force	12.5 N
Idling speed	3000 rpm
Maximum power speed	8000 rpm
Max engine/motor	10000 rpm
Output shaft power	0.8 kW
Vac bag capacity	64.35 l
<b>CERTIFICATIONS</b>	
Cert machine dir. 2006/42/EC Decl. No.	YES
Commercial Warranty	90 Days
Homeowner Warranty	2 Years
<b>DIMENSIONS</b>	
Article gross weight	8000 g
Article net weight	4000 g
Tube diameter	65.0 mm
Tube length	641.0 mm
Weight (complete product w/o side packed articles)	4.35 kg
<b>ENGINE</b>	
Carburetor	Zama C1Q
Cylinder bore	35 mm
Cylinder displacement	28 cm <sup>3</sup>
Cylinder stroke	28.7 mm
Electrode gap	0.6 mm
Engine Family CARB	*PWES.0284BQ
Engine Family EPA	*PWES.0284BQ
Fuel tank volume	0.5 l
Fuel consumption	575 g/kWh
Idling speed	3000 rpm
Maximum power speed	8000 rpm
Output shaft power	0.8 kW
Spark Plug	Champion RCJ6Y
<b>EQUIPMENT</b>	
Harness	Single harness
Nozzle type	Round+ Flat
Vacuum Kit	Yes
<b>LUBRICANTS</b>	
Fuel consumption	575 g/kWh
Fuel tank volume	0.5 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type	Petrol
<b>MATERIALS</b>	
Master pack: Paper material	0 g
Metal total	0 g
Paper (PAP 22)	0 g
Paper material total	1080 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total	8 g
Plastic rigid total	0 g
Plastic total	8 g
PS/EPS/HIPS (06) total	0 g
<b>PACKAGING</b>	
Packaging height	480 mm
Packaging length	530 mm
Packaging volume	7.1232 dm <sup>3</sup>
Packaging width	280 mm
Pallet layers	2
Quantity in Master pack	1
<b>EMISSION DATA</b>	
Exhaust emissions (CO average) EU	138 g/kWh
Exhaust emissions (CO average) EPA	168 g/kWh

**Technical Specifications**

Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (CO average) EU	1457 g/kWh
Exhaust emissions (CO EU V)	1392 g/kWh
Exhaust emissions (HC average) EU	28 g/kWh
Exhaust emissions (HC average) EPA	41.5 g/kWh
Exhaust emissions (NOx average) EU	1 g/kWh
Exhaust emissions (NOx average) EPA	0.4 g/kWh
<b>EMISSION DATA CARB</b>	
Engine Family CARB	*PWES.0284BQ
<b>EMISSION DATA EPA</b>	
Exhaust emissions (CO average) EPA	168 g/kWh
Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (HC average) EPA	41.5 g/kWh
Exhaust emissions (NOx average) EPA	0.4 g/kWh
<b>EMISSION DATA EU</b>	
Exhaust emissions (CO average) EU	138 g/kWh
Exhaust emissions (CO average) EU	1457 g/kWh
Exhaust emissions (HC average) EU	28 g/kWh
Exhaust emissions (NOx average) EU	1 g/kWh
<b>SOUND AND NOISE</b>	
Sound level	112 dB(A)
Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	109 dB(A)
Sound pressure (15m)	70 dB(A)
Sound pressure level at operators ear	94 dB(A)
<b>VIBRATIONS</b>	
Equivalent vibration level (ahv, eq) handle	11.1 m/s <sup>2</sup>