



Husqvarna 125B

An efficient hand held leaf blower that combines high blowing power with user friendliness. Perfect for home owners. Well balanced and easy to manoeuvre thanks to the in-line air outlet.



Easy starting

Air purge for very easy starting.



Adjustable Tube Length

Easily adjust the blowing tube length for maximum performance

Multi-Speed Control

Variable speed throttle with cruise control option for easier handling



Ergonomic Balanced Design

Balanced for less strain on your arms, shoulders and back



FEATURES

- Variable speed throttle with cruise control option for easier handling
- Easily adjust the blowing tube length for maximum performance
- Air purge removes air from carburetor and fuel system for easy starting
- Balanced for less strain on your arms, shoulders and back
- Stop switch automatically resets to ON so blower is ready for next use
- 470 CFM for maximum blowing performance at only 9.4 lbs

Technical Specifications	
CAPACITY	
Air flow in housing	13.31 m ³ /min
Air flow in pipe	12.03 m ³ /min
Air speed	76 m/s
Air speed (flat nozzle)	76 m/s
Air speed (round nozzle)	58.12 m/s
Blow speed	217 km/h
Blowing Force	12.5 N
Idling speed	3000 rpm
Maximum power speed	8000 rpm
Max engine/motor	10000 rpm
Output shaft power	0.8 kW
CERTIFICATIONS	
Cert machine dir. 2006/42/EC Decl. No.	YES
Commercial Warranty	90 Days
Homeowner Warranty	2 Years
DIMENSIONS	
Article gross weight	7802 g
Article net weight	4000 g
Tube diameter	65.0 mm
Tube length	641.0 mm
Weight (complete product w/o side packed articles)	4.26 kg
ENGINE	
Carburetor	Zama C1Q
Cylinder bore	35 mm
Cylinder displacement	28 cm ³
Cylinder stroke	28.7 mm
Electrode gap	0.6 mm
Engine Family CARB	*PWES.0284BQ
Engine Family EPA	*PWES.0284BQ
Fuel tank volume	0.5 l
Fuel consumption	575 g/kWh
Idling speed	3000 rpm
Maximum power speed	8000 rpm
Output shaft power	0.8 kW
Spark Plug	Champion RCJ6Y
EQUIPMENT	
Harness	Not included
Nozzle type	Round+ Flat
Vacuum Kit	No
LUBRICANTS	
Fuel consumption	575 g/kWh
Fuel tank volume	0.5 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type	Petrol
MATERIALS	
Master pack: Paper material	0 g
Metal total	0 g
Paper (PAP 22)	1900 g
Paper material total	1900 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total	0 g
Plastic rigid total	130 g
Plastic total	130 g
PS/EPS/HIPS (06) total	0 g
PACKAGING	
Packaging height	470 mm
Packaging length	533 mm
Packaging volume	7.1646 dm ³
Packaging width	286 mm
Quantity in Master pack	1
EMISSION DATA	
Exhaust emissions (CO average) EU	15.4 g/kWh
Exhaust emissions (CO average) EPA	165.19 g/kWh
Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (CO average) EU	1392 g/kWh
Exhaust emissions (CO EU V)	1392 g/kWh

Technical Specifications

Exhaust emissions (HC average) EU	36.3 g/kWh
Exhaust emissions (HC average) EPA	34.24 g/kWh
Exhaust emissions (NOx average) EU	1.8 g/kWh
Exhaust emissions (NOx average) EPA	0.29 g/kWh
EMISSION DATA CARB	
Engine Family CARB	*PWES.0284BQ
EMISSION DATA EPA	
Exhaust emissions (CO average) EPA	165.19 g/kWh
Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (HC average) EPA	34.24 g/kWh
Exhaust emissions (NOx average) EPA	0.29 g/kWh
EMISSION DATA EU	
Exhaust emissions (CO average) EU	15.4 g/kWh
Exhaust emissions (CO average) EU	1392 g/kWh
Exhaust emissions (HC average) EU	36.3 g/kWh
Exhaust emissions (NOx average) EU	1.8 g/kWh
SOUND AND NOISE	
Sound level	112 dB(A)
Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	109 dB(A)
Sound pressure (15m)	70 dB(A)
Sound pressure level at operators ear	94 dB(A)
VIBRATIONS	
Equivalent vibration level (ahv, eq) handle	11.1 m/s ²