



Husqvarna Z242E

Performance and style hit the grass running with the all new Z200 Series Zero Turn Mowers. Husqvarna ZTR mowers offer cutting edge design, proven performance and new innovative features combine to make lawn maintenance an event instead of a chore. Packed with features including high performance Clear Cut™ fabricated cutting deck, Removable foot plate, Rear engine guard and Anti-slip foot area.



Rear engine guard

The rear guard protects the engine from impact as well as limits access to hot surfaces for safety.




Removable Foot Plate

Quick access to cutting deck for easy maintenance and clean-up

Premium Integrated Transmission

Lasts longer with reduced maintenance thanks to zero-turn specific features



Dust protection

Rubber bellows prevent debris and moisture from entering the control system



FEATURES

- Lasts longer with reduced maintenance thanks to zero-turn specific features
- Quick access to cutting deck for easy maintenance and clean-up
- Rear engine guard
- Dust protection
- Brake automatically engages and disengages as steering levers are moved in and out
- Ergonomic control panel
- No turning radius by individual wheel-drive
- Bumper
- Delivers smooth, quiet and reliable power with heavy-duty components for a long life
- Anti-slip foot area
- Easy to use and spring-assisted for reduced effort
- Specially-designed 42 in. deck built for superior cutting performance whether discharging, bagging or mulching
- Rugged frame and wheels ensure durability and long-lasting performance

Technical Specifications	
BATTERY	
Battery capacity	18 Ah
Battery type	Lead-Acid
Battery voltage	12 V
CAPACITY	
Blade-tip speed	93.98 m/s
Output shaft power	21.5 hp
DIMENSIONS	
Article gross weight	326.133 g
Base machine, height	101.6 cm
Base machine, length	190.5 cm
Base machine, width (chute down)	142.24 cm
Base machine, width (chute up)	122 cm
Base machine, width	105.4 cm
Cutting height steps	6
Deck thickness	3.5 mm
Seat back height	High
Weight (complete product w/o side packed articles)	254 kg
ENGINE	
Cylinder displacement	726 cm ³
Cylinders	2
Engine cooling	Air
Engine name	FR Series
Fuel tank volume	13.25 l
Fuel tank volume	3.5 gal (US)
Motor/engine manufacturer	Kawasaki
Motor/engine model	FR 651V
EQUIPMENT	
12V outlet	No
Air filter type	Paper
All-Wheel Drive (AWD)	No
Anti-scalp wheels	1
Blade brake clutch (BBC)	Yes
Blade engagement	Electric clutch
Blades	2 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	10-gauge fabricated
Cutting methods	3-in-1 Mulch/Rear Bag/Side Discharge Capable
Deck lifting system	Manual, hand operated
Deck Wash Port	Yes
Deflector	Included
Drive method	Lever-operated
Drive system	Rear wheel drive
Drive wheels	Rear
Electric start	Yes
Hinged armrests	Optional
Hour meter type	Digital with pre-programmed service intervals
Hydraulic equipment lift	No
Nose roller	Yes
Seat spring	Yes
Seat type	15" high back
Throttle control	Yes
LUBRICANTS	
Engine lubrication type	Full pressure
Fuel consumption	0.0733 l/min
Fuel tank location	Side (Single)
Oil capacity	2.1 l
Oil cooler	No
Oil filter	Yes
Power/fuel type	Gasoline

Technical Specifications

MATERIALS	
Cutting deck material	Steel
Master pack: Paper material	0 g
Metal total	1200 g
Paper material total	0 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total	450 g
Plastic rigid total	900 g
Plastic total	1350 g
Powder-coated cutting deck	Yes
PS/EPS/HIPS (06) total	0 g
Seat material	Vinyl
Spindle/mandrel type	Cast iron
PACKAGING	
Quantity in Master pack	1
SOUND AND NOISE	
Sound level	104 dB(A)
Sound power level, guaranteed (LWA)	105 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	88 dB(A)

ACCESSORIES



ZTR® ZERO TURN DOUBLE BIN
COLLECTION SYSTEM
587 41 24-01