




Husqvarna 525BX

A powerful and well-balanced handheld Husqvarna blower for professional use. The patented X-torq engine technology in combination with the special fan and housing design means high blowing capacity that is easy to control. The 525BX commercial leaf blower features an anti-vibration system 'Low Vib' making work less strenuous – even during long shifts. And all intuitive controls, i.e. Cruise Control, contribute to efficient and convenient operation at all times.



Simple Starting

When the stop switch has been used, it is automatically reset to ON to facilitate the next start.




Adjustable Tube Length

Easily adjust the blowing tube length for maximum performance

Powerful and Efficient X-TORQ® Engine

Our X-TORQ® engines deliver great power and torque thanks to highly efficient combustion.



Easy starting

Air purge for very easy starting.



FEATURES

- Great power and efficiency
- Easily adjust the blowing tube length for maximum performance
- When the stop switch has been used, it is automatically reset to ON to facilitate the next start.
- Air purge removes air from carburetor and fuel system for easy starting
- Variable speed throttle with cruise control option for easier handling
- Easy to operate with in lined air outlet

Technical Specifications	
CAPACITY	
Air flow in housing	14 m ³ /min
Air flow in pipe	13 m ³ /min
Air speed (flat nozzle)	86 m/s
Air speed (round nozzle)	70 m/s
Blowing Force	15 N
Idling speed	3000 rpm
Maximum power speed	7300 rpm
Output shaft power	0.81 kW
Torque, max.	1.15 Nm
Torque, max. at rpm	6000 rpm
DIMENSIONS	
Article gross weight	7660 g
Article net weight	6500 g
Tube diameter	68 mm
Tube length	550 mm
Weight (complete product w/o side packed articles)	4.4 kg
ENGINE	
Cylinder bore	34 mm
Cylinder displacement	25.4 cm ³
Cylinder stroke	28 mm
Electrode gap	0.65 mm
Engine Family CARB	FHQZS.0254GQ
Engine Family EPA	FHQZS.0254GQ
Fuel tank volume	0.45 l
Fuel consumption	550 g/kWh
Idling speed	3000 rpm
Ignition module air gap	0.3 mm
Maximum power speed	7300 rpm
Output shaft power	0.81 kW
Spark Plug	NGK BPMR8Y
EQUIPMENT	
Nozzle type	Round+ Flat
Vacuum Kit	No
LUBRICANTS	
Fuel consumption	550 g/kWh
Fuel tank volume	0.45 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Power/fuel type	Petrol
MATERIALS	
Master pack: Paper material	0 g
Metal total	0 g
Paper (PAP 22)	131 g
Paper material total	131 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total	0 g
Plastic rigid total	0 g
Plastic total	0 g
PS/EPS/HIPS (06) total	0 g
PACKAGING	
Packaging height	400 mm
Packaging length	460 mm
Packaging volume	71.76 dm ³
Packaging width	390 mm
Pallet layers	5
Quantity in Master pack	1
EMISSION DATA	
Exhaust emissions (CO average) EU	379.85 g/kWh
Exhaust emissions (CO average) EU	988 g/kWh
Exhaust emissions (CO EU V)	1110 g/kWh
Exhaust emissions (HC average) EU	25.99 g/kWh
Exhaust emissions (NOx average) EU	0.29 g/kWh
EMISSION DATA CARB	
Engine Family CARB	FHQZS.0254GQ
EMISSION DATA EU	
Exhaust emissions (CO average) EU	379.85 g/kWh
Exhaust emissions (CO average) EU	988 g/kWh

Technical Specifications

Exhaust emissions (HC average) EU	25.99 g/kWh
Exhaust emissions (NOx average) EU	0.29 g/kWh

SOUND AND NOISE

Sound power level, guaranteed (LWA)	106 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure (15m)	71 dB(A)
Sound pressure level at operators ear	91 dB(A)

VIBRATIONS

Daily Vibration (Aeqv)	1.2 m/s ²
Daily Vibration Exposure (A8)	0.5 m/s ²
Daily Vibration Time (Time factor)	1.5 h
Equivalent vibration level (ahv, eq) handle	1.2 m/s ²