




## Husqvarna 129C

Husqvarna grass trimmer 129C facilitates demanding trimming tasks with its powerful 27cc engine. The trimmer is equipped with Smart Start®, which provides a smooth and quick start with minimal effort. The user experience is also improved by the intuitive controls and the auto return stop switch, which is automatically reset to the ON position after it has been used. 129C comes with a curved shaft for comfortable trimming.



### Long curved shaft

Extra long curved shaft for extended reach and superior ergonomics.



### Simple Starting

When the stop switch has been used, it is automatically reset to ON to facilitate the next start.

### Intuitive controls

All controls are designed to be easy to understand and use.



### Easy starting

Air purge for very easy starting.



## FEATURES

- All controls are designed to be easy to understand and use.
- When the stop switch has been used, it is automatically reset to ON to facilitate the next start.
- Extra long curved shaft for extended reach and excellent ergonomics.
- Air purge removes air from carburetor and fuel system for easy starting
- Specially-designed engine and starter for easy and fast starting with minimum effort
- Transparent fuel tank makes it easy to check the fuel level.
- Comfortable curved handle and shaft for easier use and increased maneuverability

Technical Specifications	
<b>CAPACITY</b>	
Clutch engagement speed ( $\pm 120$ )	4200 rpm
Clutch engagement upper limit	4320 rpm
Idling speed	2800 rpm
Idling upper limit	3200 rpm
Maximum power speed	8000 rpm
Maximum rpm output shaft	8000 rpm
Output shaft thread	3/8"-24H
Output shaft power	0.85 kW
Torque, max.	1.1 Nm
Torque, max. at rpm	6000 rpm
<b>CERTIFICATIONS</b>	
Cert machine dir. 2006/42/EC Decl. No.	YES
<b>DIMENSIONS</b>	
Article gross weight	8970 g
Article net weight	6125 g
Cutting width	43 cm
Tube length	1340 mm
Tube diameter	25.4 mm
Weight (excl. cutting equipment)	4.49 kg
<b>ENGINE</b>	
Cylinder bore	36 mm
Cylinder displacement	27.6 cm <sup>3</sup>
Cylinder stroke	27 mm
Electrode gap	0.5 mm
Engine Family CARB	*PWES.0284TJ
Engine Family EPA	*PWES.0284TJ
Ignition module air gap	0.3 mm
Spark Plug	Husqvarna HQT-4 672201
<b>EQUIPMENT</b>	
Air filter type	Foam
Drive gear angle	0°
Gear ratio	0
Handle type	Loop
Grass blade	Not included
Harness	Not included
Saw blade	Not included
Trimmer head	R25
Output shaft thread	3/8"-24H
<b>LUBRICANTS</b>	
Fuel consumption	495 g/kWh
Fuel tank volume	0.34 l
Lubricant type (bevel gear)	Mineral grease
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
<b>PACKAGING</b>	
Packaging height	268 mm
Packaging length	1572 mm
Packaging width	267 mm
Quantity in Master pack	1
<b>EMISSION DATA CARB</b>	
Engine Family EPA	*PWES.0284TJ
Engine Family CARB	*PWES.0284TJ
Exhaust emissions (CO average) CARB	30.3 g/kWh
Exhaust emissions (CO average) CARB	1433 g/kWh
Exhaust emissions (HC average) CARB	31.56 g/kWh
Exhaust emissions (NOx average) CARB	1.82 g/kWh
<b>EMISSION DATA EPA</b>	
Exhaust emissions (CO average) EPA	30.3 g/kWh
Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (CO average) EPA	1433 g/kWh
Exhaust emissions (HC average) EPA	31.56 g/kWh
Exhaust emissions (NOx average) EPA	1.82 g/kWh
<b>EMISSION DATA EU</b>	
Exhaust emissions (CO average) EU	43.3 g/kWh
Exhaust emissions (CO average) EU	1504 g/kWh

**Technical Specifications**

Exhaust emissions (CO EU V)	1504 g/kWh
Exhaust emissions (HC average) EU	28.2 g/kWh
Exhaust emissions (NOx average) EU	2.1 g/kWh

**MATERIALS**

Master pack: Paper material	0 g
Metal total	0 g
Other plastic: rigid	0
Paper (PAP 22)	0 g
Paper material total	2463 g
HDPE (O2) total	0 g
PET (O1) total	0 g
Plastic foil total	0 g
Plastic rigid total	0 g
Plastic total	0 g
PS/EPS/HIPS (O6) total	0 g

**SOUND AND NOISE**

Sound power level, guaranteed (LWA)	114 dB(A)
Sound power level, measured	106 dB(A)
Sound pressure level at operators ear	93 dB(A)

**VIBRATIONS**

Daily Vibration (Aeqv)	3.7 m/s <sup>2</sup>
Daily Vibration Exposure (A8)	3.7 m/s <sup>2</sup>
Daily Vibration Time (Time factor)	2 h
Equivalent vibration level (ahv, eq) front handle	3.64 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) left handle	3.7 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) rear handle	3.59 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) right handle	3.6 m/s <sup>2</sup>