




Husqvarna 129LK

Husqvarna 129LK is a multi-purpose combi trimmer that handles a variety of tasks with its powerful 27cc engine. The trimmer is equipped with Smart Start®, which provides a smooth and quick start with minimal effort. The user experience is also improved by the intuitive controls and the auto return stop switch, which is automatically reset to the ON position after it has been used. Apart from the trimmer head, 129LK can easily be equipped with a number of other tools: blower, pole saw, cultivator, hedge trimmer, and edger, by changing the lower part of the shaft.



Easy starting

Air purge for very easy starting.



Simple Starting

When the stop switch has been used, it is automatically reset to ON to facilitate the next start.

Intuitive controls

All controls are designed to be easy to understand and use.



Smart Start® Technology

Specially-designed engine and starter for easy and fast starting with minimum effort. Resistance in the starter cord is reduced by up to 40%.



FEATURES

- All controls are designed to be easy to understand and use.
- When the stop switch has been used, it is automatically reset to ON to facilitate the next start.
- Air purge removes air from carburetor and fuel system for easy starting
- Specially-designed engine and starter for easy and fast starting with minimum effort
- Transparent fuel tank makes it easy to check the fuel level.
- With Tap'n Go, line feeding is done effortlessly by simply pushing the trimmer head into the ground.
- Easily breaks down for safer transport and compact storage
- Versatile product thanks to the numerous tools available as accessories.
- Easy to change attachments to adapt the product to different tasks.

Technical Specifications	
CAPACITY	
Clutch engagement speed (± 120)	4200 rpm
Clutch engagement upper limit	4320 rpm
Idling speed	2800 rpm
Idling upper limit	3200 rpm
Maximum power speed	8000 rpm
Maximum rpm output shaft	7200 rpm
Output shaft thread	M10x1.25 Lefthanded
Output shaft power	0.85 kW
Torque, max.	1.1 Nm
Torque, max. at rpm	6000 rpm
CERTIFICATIONS	
Cert machine dir. 2006/42/EC Decl. No.	Yes
DIMENSIONS	
Article gross weight	8960 g
Article net weight	7110 g
Cutting width	43 cm
Tube length	1483 mm
Tube diameter	25.4 mm
Weight (excl. cutting equipment)	4.67 kg
ENGINE	
Cylinder bore	36 mm
Cylinder displacement	27.6 cm ³
Cylinder stroke	27 mm
Electrode gap	0.5 mm
Engine Family CARB	*PWES.0284TJ
Engine Family EPA	*PWES.0284TJ
Ignition module air gap	0.3 mm
Spark Plug	NGK CMR6A
EQUIPMENT	
Air filter type	Foam
Drive gear angle	30°
Gear ratio	0.68
Handle type	Loop
Grass blade	Not included
Harness	Not included
Saw blade	Not included
Trimmer head	R25
Output shaft thread	M10x1.25 Lefthanded
LUBRICANTS	
Fuel consumption	495 g/kWh
Fuel tank volume	0.34 l
Lubricant type (bevel gear)	Mineral grease
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
PACKAGING	
Packaging height	272 mm
Packaging length	1016 mm
Packaging width	255 mm
Quantity in Master pack	1
EMISSION DATA CARB	
Engine Family EPA	*PWES.0284TJ
Engine Family CARB	*PWES.0284TJ
Exhaust emissions (CO average) CARB	30.3 g/kWh
Exhaust emissions (CO average) CARB	1433 g/kWh
Exhaust emissions (HC average) CARB	31.56 g/kWh
Exhaust emissions (NOx average) CARB	1.82 g/kWh
EMISSION DATA EPA	
Exhaust emissions (CO average) EPA	30.3 g/kWh
Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (CO average) EPA	1433 g/kWh
Exhaust emissions (HC average) EPA	31.56 g/kWh
Exhaust emissions (NOx average) EPA	1.82 g/kWh
EMISSION DATA EU	

Technical Specifications

Exhaust emissions (CO average) EU	43.3 g/kWh
Exhaust emissions (CO average) EU	1504 g/kWh
Exhaust emissions (CO EU V)	1504 g/kWh
Exhaust emissions (HC average) EU	28.2 g/kWh
Exhaust emissions (NOx average) EU	2.1 g/kWh

MATERIALS

Master pack: Paper material	0 g
Metal total	0 g
Other plastic: rigid	0
Paper (PAP 22)	0 g
Paper material total	1998 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total	0 g
Plastic rigid total	0 g
Plastic total	0 g
PS/EPS/HIPS (06) total	0 g

SOUND AND NOISE

Sound power level, guaranteed (LWA)	114 dB(A)
Sound power level, measured	106 dB(A)
Sound pressure level at operators ear	95 dB(A)

VIBRATIONS

Daily Vibration (Aeqv)	6.24 m/s ²
Daily Vibration Exposure (A8)	6.24 m/s ²
Daily Vibration Time (Time factor)	2 h
Equivalent vibration level (ahv. eq) left handle	6.24 m/s ²
Equivalent vibration level (ahv. eq) rear handle	8.79 m/s ²
Equivalent vibration level (ahv. eq) right handle	8.9 m/s ²