



Husqvarna Z554L

The Husqvarna Z500 series zero turn mower represents the latest design focused on productivity, durability and cut quality. Providing extreme comfort, high ground speeds and superior traction adds up to exceptional mowing efficiency. Industrial strength throughout the entire design assures of a long & durable service life in commercial mowing applications. Careful design consideration provides unprecedented ease in serviceability.



LED fuel gauge

The automotive style LED fuel gauge lets you know exactly how much fuel is remaining and warns you when you are too low.



AGM Battery

A smaller and more robust battery adopted from the transportation industry provides better reliability, improved longevity and more service space.

Cast aluminium spindles

10" diameter commercial cast aluminium spindles with tapered roller bearings more effectively spread impact loads for extended durability.



Heavy duty fabricated cutting deck

A deep draw deck, heavy duty cutting blades and an efficient flow design allow for rapid cut speeds with a high quality finish.



FEATURES


- Cast aluminium spindles
- AGM Battery
- Automotive style LED fuel gauge
- Heavy duty fabricated cutting deck
- Automatic parking brake
- The discharge chute is built of heavy-duty rubber to withstand wear and tear while protecting nearby property.
- HydroGear ZT5400 Transmissions handles even the biggest jobs in landscaping
- Deck height adjustment
- Easily foldable ROPS protects the user
- Large fuel capacity
- Comfortable, user-focused controls put everything needed to operate the mower within easy reach.
- Premium suspension seat for increased comfort

Technical Specifications	
BATTERY	
Battery capacity	12 Ah
Battery type	Lead-Acid
Battery voltage	12 V
CAPACITY	
Output shaft power	27.0 hp
DIMENSIONS	
Article gross weight	661791 g
Article net weight	544764 g
Base machine, height	117 cm
Base machine, length	206 cm
Base machine, width (chute down)	173 cm
Base machine, width (chute up)	140 cm
Base machine, width	136 cm
Cutting height steps	16
Seat back height	Extra high 21"
Weight (complete product w/o side packed articles)	551 kg
ENGINE	
Cylinder displacement	852 cm ³
Cylinders	2
Engine cooling	Air
Engine name	FX Series V-Twin
Fuel tank volume	45.4 l
Fuel tank volume	11.99 gal (US)
Motor/engine manufacturer	Kawasaki
Motor/engine model	FX850V
EQUIPMENT	
Air filter type	Heavy-Duty Canister Style
Anti-scalp wheels	2
BioClip® kit	Available as accessory
Blade engagement	Electric clutch
Blade type	High Performance
Blades	3 pcs
Collector	Available as accessory
Cup holder	Yes
Cutting deck type	10-gauge fabricated
Cutting methods	Collect/Mulch/Side discharge
Deck lifting system	Manual, foot activated
Deck Wash Port	No
Drive method	Lever-operated
Drive system	Rear wheel drive
Drive wheels	Rear
Electric start	Yes
Headlights	No
Hinged armrests	Standard
Hour meter type	Digital with pre-programmed service intervals
Nose roller	No
Parking brake, type	Integrated
Seat type	Premium, suspension
LUBRICANTS	
Engine lubrication type	Full pressure with oil filter
Fuel consumption	0.1067 l/min
Fuel tank location	Side (Dual)
Oil capacity	2.3 l
Oil filter	Yes
Power/fuel type	Gasoline
MATERIALS	
Cutting deck material	Steel
Master pack: Paper material	0 g
Metal total	0 g
Paper material total	0 g
HDPE (O2) total	1050 g

Technical Specifications

PET (01) total	0 g
Plastic foil total	525 g
Plastic rigid total	525 g
Plastic total	1050 g
Powder-coated cutting deck	Yes
PS/EPS/HIPS (06) total	0 g
Seat material	Vinyl
Spindle/mandrel type	Aluminium commercial
PACKAGING	
Packaging height	1346 mm
Packaging length	2172 mm
Packaging width	1740 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	105 dB(A)
Sound power level, measured	104 dB(A)
Sound pressure level at operators ear	85 dB(A)

ACCESSORIES



DRIVE KIT
966 40 71-01

HUSQVARNA MULCH KIT 54"
598 39 05-01

OPERATOR CONTROLLED
DISCHARGE CHUTE (OCDC)
966 48 87-01