

HUSQVARNA 120iB - Skin Only

Husqvarna 120iB is a lightweight and easy-to-use battery-powered leaf blower, suitable for small and medium gardens. Three different modes enable optimal performance based on needs, from light tasks to tasks requiring full power. The compact design, softgrip, low weight and perfect balance provide excellent ergonomics for comfortable work.



Excellent ergonomics

Superb product balance, comfortable handle grip, and intuitive keypad provide excellent ergonomics for comfortable work.

3 different modes for best perfomance depending on need or task.

Three modes give you an optimal performance based on needs, from light tasks to tasks requiring full power. 3N for more minor duties inside or outside. 7N for good power, suitable for most tasks. 10N for tougher duties and when full power is needed.



Efficient Brushless Motor

Brushless motor for higher efficiency, longer lifetime, and less maintenance compared to brushed motors. Since there are no brushes, friction is eliminated, no energy is lost, and the motor runs cooler. This also eliminates the need for maintenance or replacement of worn brushes, and you can benefit from improved performance and higher torque.

Fast acceleration when starting

Fast acceleration when starting, makes the job more efficient.

FEATURES

- Three modes give you an optimal performance based on needs, from light tasks to tasks requiring full power.
- Fast acceleration when starting
- Superb product balance and grip, and intuitive keypad, provide excellent ergonomics for comfortable work.
- Brushless motor for higher efficiency, longer lifetime and less maintenance compared to brushed motors.
- Husqvarna's flexible 36V system BLi-X offers battery power for everything from light and demanding homeowner tasks to professional use.
- Low noise levels create pleasant work and enable longer working hours without disturbing others.
- This product does not emit CO emissions during use.

BATTERY	
	Ma
Pattery shareer	No Not included
attery charger attery type	Li-lon
attery type attery voltage	36 V
umber of batteries included	0
	U U
APACITY	400 2/ 1
ir flow in pipe	10.3 m³/min
ir flow in pipe	618 m³/h
ir speed	46 m/s
ir speed (round nozzle)	46 m/s
lowing Force	9.6 N
IMENSIONS	
rticle gross weight	2838 g
rticle net weight	2143 g
ube diameter	69 mm
ube length	425 mm
/eight (excl. battery)	2.0 kg
NGINE	
fotor type	BLDC (brushless)
QUIPMENT	
larness	Single harness
ozzle type	Round
acuum Kit	No
UBRICANTS	
Power/fuel type	Battery
MATERIALS	,
Master pack: Paper material	0 g
Metal total	0 g
Paper (PAP 22)	1266 g
aper material total	1266 g
IDPE (02) total	0 g
ET (01) total	0 g
lastic foil total	0 g
Plastic rigid total	2 g
Plastic total	2 g
S/EPS/HIPS (06) total	0 g
ACKAGING	
Packaging height	194 mm
ackaging length	324 mm
ackaging width	534 mm
luantity in Master pack	1
OUND AND NOISE	•
ound power level, guaranteed (LWA)	96.6 dB(A)
ound power level, guaranteed (LWA) ound power level, measured	95.6 dB(A) 95.7 dB(A)
ound pressure level at operators ear	95.7 dB(A) 83 dB(A)
	O3 UB(A)
IBRATIONS (1)	4.40
ally Vibration (Aeqv)	1 m/s²
aily Vibration Exposure (A8)	0.61 m/s²
aily Vibration Time (Time factor)	3 h