



HUSQVARNA TR 348

The TR 348 is a light-weight, compact and easy to use tiller with great manoeuvrability. Equipped with a high-quality transmission, Heli coiled tines and a 48 cm working width it offers both great performance and durability.



Foldable handlebar

For easy storage and transport.



Drag bar

Easy-adjust drag bar, for balance in different working conditions.

Adjustable handlebar

Adjustable handlebar, both horizontally and vertically, for best working position.



Handlebar-mounted gear selection

Ergonomic handle with easy-access controls.



FEATURES

- Adjustable handlebar, both horizontally and vertically, for best working position.
- Drag bar for balanced operation
- Foldable handlebar for easy storage
- Ergonomic handle with easy-access controls
- Tine shield for minimized debris spray
- Reverse gear for optimum maneuverability

| Technical Specifications | |
|--|---------------------|
| CAPACITY | |
| Net power at preset rpm | 3300 rpm |
| Net power at preset rpm Energy | 4.5 kW |
| Rotational speed (min/max) max | 207 rpm |
| Rotational speed (min/max) min | 103 rpm |
| Rotational speed | 3300 rpm |
| DIMENSIONS | |
| Article gross weight | 74000 g |
| Article net weight | 71000 g |
| Tine diameter | 300 mm |
| Tyre size | 345 mm |
| Weight (complete product w/o side packed articles) | 73 kg |
| Working depth | 15 cm |
| Working width | 48 cm |
| ENGINE | |
| Cylinder displacement | 208 cm ³ |
| Engine brand | Briggs and Stratton |
| Engine name | 950 Series |
| Fuel tank volume | 3.6 l |
| Fuel tank volume | 0.95 gal (US) |
| Motor/engine manufacturer | Briggs & Stratton |
| Transmission steps forward | 2 |
| Transmission steps reverse | 1 |
| Transmission type | Chain/Gear |
| Transport wheel/s | Not available |
| EQUIPMENT | |
| Chevron tyres | No |
| Cultivator type | Rear-tine |
| Drag bar | Yes |
| Foldable handlebar | Yes |
| Handlebar-mounted gear selection | No |
| Horizontally adjustable handlebar | Yes |
| Plant guards | No |
| Reverse gearbox | Yes |
| Rubber wheels | Included |
| Transport wheel/s | Not available |
| Vertically adjustable handlebar | Yes |
| LUBRICANTS | |
| Fuel consumption | 505 g/kWh |
| Fuel tank volume | 3.6 l |
| Power/fuel type | Petrol |
| MATERIALS | |
| Master pack: Paper material | 0 g |
| Metal total | 0 g |
| Paper material total | 0 g |
| HDPE (02) total | 0 g |
| PET (01) total | 0 g |
| Plastic foil total | 0 g |
| Plastic rigid total | 0 g |
| Plastic total | 0 g |
| PS/EPS/HIPS (06) total | 0 g |
| PACKAGING | |
| Packaging height | 790 mm |
| Packaging length | 1150 mm |
| Packaging width | 600 mm |
| Quantity in Master pack | 1 |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 98 dB(A) |
| Sound power level, measured | 95.3 dB(A) |
| Sound pressure level at operators ear | 84.5 dB(A) |