




Husqvarna 130

The reliable Husqvarna 130 chainsaw is easy to start, easy to handle and developed for garden tasks like cutting firewood, pruning or felling small trees. The LowVib® technology reduces vibrations so you can work more comfortably, and the efficient X-Torq® engine delivers great power and torque thanks to highly efficient combustion. In addition, it is easy to maintain thanks to Air Injection™ which keeps the filter cleaner for longer. In case of a kickback, the effective inertia-activated chain brake immediately stops the chain to reduce the likelihood of injury.



Inertia-Activated Chain Brake

In case of a kickback, the effective inertia-activated chain brake immediately stops the chain to reduce the likelihood of injury.



Powerful and Efficient X-TORQ® Engine

Delivers lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.

Air Injection™ Technology

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleaning.



Quick Start with Air Purge

Air purge removes air from carburetor and fuel system for easy starting



FEATURES

- Centrifugal air cleaning system expels larger dust and debris particles before they reach the air filter to help improve engine life
- Great power and efficiency
- Effective inertia-activated chain brake reduces the likelihood of injury due to kickback.
- Air purge removes air from carburetor and fuel system for easy starting
- Provides easier starting and reduces the risk of engine flooding
- Effective LowVib® dampeners absorb vibration, sparing the user's arms and hands.

Technical Specifications	
CAPACITY	
Chain speed at 133% of maximum engine power speed	22.3 m/s
Chain speed at max power	16.8 m/s
Clutch engagement speed (±120)	4000 rpm
Clutch engagement upper limit	4500 rpm
Idling speed	3000 rpm
Idling upper limit	3200 rpm
Ignition module air gap	0.3 mm
Maximum power speed	9000 rpm
Output shaft power	1.5 kW
Racing speed lower limit	11200 rpm
Torque, max.	1.84 Nm
Torque, max. at rpm	8000 rpm
CERTIFICATIONS	
Cert machine dir. 2006/42/EC Decl. No.	NO
DIMENSIONS	
Article gross weight	6920 g
Article net weight	5620 g
Bar length (inch)	16 in
Bar length	40 cm
Weight (excl. cutting equipment)	4.7 kg
ENGINE	
Cylinder bore	39 mm
Cylinder displacement	38 cm ³
Cylinder stroke	32 mm
Electrode gap	0.55 mm
Engine Family CARB	*PWES.0384CX
Engine Family EPA	-PWES.0384CX
Ignition module air gap	0.3 mm
Spark Plug	NGK BPR7A
EQUIPMENT	
Bar mount type	HSM
Chain type	H37
Chainsaw sub-group	Occasional use chainsaws
Gauge	1.3 mm
Handle type	Standard
Pitch	3/8" mini
Sprocket type	Spur 6
LUBRICANTS	
Fuel consumption	725 g/kWh
Fuel consumption	0.725 kg/h
Fuel tank volume	0.37 l
Lubricant type (Engine)	Husqvarna 2 stroke or equiv. at 50:1
Oil pump type	Automatic
Oil tank volume	.260 l
Power/fuel type	Gasoline
MATERIALS	
Master pack: Paper material	0 g
Metal total	0 g
Paper material total	840 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total	12 g
Plastic rigid total	0 g
Plastic total	12 g
PS/EPS/HIPS (06) total	0 g
PACKAGING	
Packaging height	333 mm
Packaging length	495 mm
Packaging width	285 mm
Quantity in Master pack	1
EMISSION DATA CARB	
Engine Family CARB	*PWES.0384CX
Exhaust emissions (CO average) CARB	330.7 g/kWh
Exhaust emissions (CO average) CARB	877 g/kWh
Exhaust emissions (HC average) CARB	40.85 g/kWh
Exhaust emissions (NOx average) CARB	1.14 g/kWh

Technical Specifications**EMISSION DATA EPA**

Engine Family EPA	-PWES.0384CX
Exhaust emissions (CO average) EPA	331 g/kWh
Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (CO average) EPA	877 g/kWh
Exhaust emissions (HC average) EPA	40.85 g/kWh
Exhaust emissions (NOx average) EPA	1.14 g/kWh

EMISSION DATA EU

Exhaust emissions (CO average) EU	278.5 g/kWh
Exhaust emissions (CO average) EU	804 g/kWh
Exhaust emissions (CO EU V)	804 g/kWh
Exhaust emissions (HC average) EU	41.7 g/kWh
Exhaust emissions (NOx average) EU	1.11 g/kWh

SOUND AND NOISE

Sound power level, guaranteed (LWA)	116 dB(A)
Sound power level, measured	114.34 dB(A)
Sound pressure (15m)	102 dB(A)
Sound pressure level at operators ear	102 dB(A)

VIBRATIONS

Equivalent vibration level (ahv, eq) front handle	3.72 m/s ²
Equivalent vibration level (ahv, eq) rear handle	5.5 m/s ²
Vibrations left/front handle	3.72 m/s ²
Vibrations right/rear handle	5.494 m/s ²