




## Husqvarna 322HD60

Handle any hedge with Husqvarna 322HD60 – a robust, double-sided hedge trimmer with a 60 cm cutter bar, hardened steel blades and high cutting speed for efficient cutting. Low weight and a handle that can be placed in several different positions provide good ergonomics and easy handling. The engine and starter are designed to be started with minimum effort.



### Intuitive choke

Starting a cold engine is easier with the intuitive choke which is easy to reach and set



### Simple Starting

When the stop switch has been used, it is automatically reset to ON to facilitate the next start.

### An efficient job starts with a sharp blade

The hardened steel blades, optimized edge angles and the high knife speed increase productivity when trimming.



### Adjustable Rear Handle

Multiple handle positions makes hedge cutting easy and comfortable



## FEATURES

- The design of the cutting blades provides efficiency.
- When the stop switch has been used, it is automatically reset to ON to facilitate the next start.
- The choke is easy to reach and understand
- Multiple handle positions makes hedge cutting easy and comfortable
- Specially-designed engine and starter for easy and fast starting with minimum effort
- Internal gears have been specially designed for long life and tested under tough conditions
- Sharp and robust cutting teeth for high productivity and long product life.
- The engine design provides a low noise level and a more pleasant working environment.

Technical Specifications	
<b>CAPACITY</b>	
Cutting speed	4400 cut/min
Idling speed	2900 rpm
Maximum power speed	7800 rpm
Output shaft power	0.7 kW
Teeth opening	30 mm
Torque, max.	0.9 Nm
Torque, max. at rpm	6000 rpm
<b>CERTIFICATIONS</b>	
Cert machine dir. 2006/42/EC Decl. No.	SEC/10/2280
<b>DIMENSIONS</b>	
Article gross weight	7500 g
Article net weight	6500 g
Knife length	60 cm
Weight (complete product w/o side packed articles)	5.2 kg
Weight (excl. cutting equipment)	5.2 kg
<b>ENGINE</b>	
Cylinder bore	32 mm
Cylinder displacement	21.7 cm <sup>3</sup>
Cylinder stroke	27 mm
Electrode gap	0.5 mm
Engine Family CARB	MHVXS.0224EB
Engine Family EPA	LHVXS.0224EB
Gear ratio	1
Ignition module air gap	0.3 mm
Spark Plug	Husqvarna HQT-4 672201
<b>LUBRICANTS</b>	
Fuel consumption	379 g/kWh
Fuel tank volume	0.3 l
Power/fuel type	Gasoline
<b>PACKAGING</b>	
Packaging height	205 mm
Packaging length	1155 mm
Packaging width	257 mm
Quantity in Master pack	1
<b>EMISSION DATA CARB</b>	
Engine Family EPA	LHVXS.0224EB
Engine Family CARB	MHVXS.0224EB
Exhaust emissions (CO average) CARB	254.87 g/kWh
Exhaust emissions (CO average) CARB	1543 g/kWh
Exhaust emissions (HC average) CARB	42.02 g/kWh
Exhaust emissions (NOx average) CARB	0.46 g/kWh
<b>EMISSION DATA EPA</b>	
Exhaust emissions (CO average) EPA	254.87 g/kWh
Exhaust emissions (CO FEL) EPA	536 g/kWh
Exhaust emissions (CO average) EPA	1543 g/kWh
Exhaust emissions (HC average) EPA	42.02 g/kWh
Exhaust emissions (NOx average) EPA	0.46 g/kWh
<b>EMISSION DATA EU</b>	
Exhaust emissions (CO average) EU	230.89 g/kWh
Exhaust emissions (CO average) EU	1528 g/kWh
Exhaust emissions (CO EU V)	1528 g/kWh
Exhaust emissions (HC average) EU	42.55 g/kWh
Exhaust emissions (NOx average) EU	0.37 g/kWh
<b>MATERIALS</b>	
Master pack: Paper material	0 g
Metal total	0 g
Paper material total	0 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total	0 g
Plastic rigid total	0 g
Plastic total	0 g

**Technical Specifications**

PS/EPS/HIPS (06) total	0 g
------------------------	-----

**SOUND AND NOISE**

Sound power level, guaranteed (LWA)	102 dB(A)
-------------------------------------	-----------

Sound power level, measured	101 dB(A)
-----------------------------	-----------

Sound pressure level at operators ear	98 dB(A)
---------------------------------------	----------

**VIBRATIONS**

Daily Vibration (Aeqv)	4.4 m/s <sup>2</sup>
------------------------	----------------------

Daily Vibration Exposure (A8)	2.9 m/s <sup>2</sup>
-------------------------------	----------------------

Daily Vibration Time (Time factor)	3.5 h
------------------------------------	-------

Equivalent vibration level (ahv, eq) front handle	4.4 m/s <sup>2</sup>
---	----------------------

Equivalent vibration level (ahv, eq) rear handle	4.3 m/s <sup>2</sup>
--	----------------------