

# **HUSQVARNA 110iL** with battery and charger

Husqvarna 110iL is the ideal battery grass trimmer for smaller gardens, operating with low noise, vibrations and no direct emissions. Designed to be extremely easy to use. This battery grass trimmer delivers superb work results, thanks to features such as auto feed trimmer head, foldable Plant Guard bracket and Edging mode with integral support wheel. The split shaft makes it very easy to transport and store.



#### Auto feed

Automatic line feed with dual lines will ensure optimal trimmer line length without effort and a more even trimming result than trimmers with one line. Husqvarna Trimmer Head A15B works perfectly for both trimming and edging. The ultimate option for versatile and carefree use.



### **Edging mode**

Simply twist the trimmer head to use the integral support wheel and benefit from increased control and precision when cutting lawn edges.



Easily switchable attachments enabling you to carry out all common garden tasks with one tool. Fits the 110iL FLXi system.



#### Interchangeable Battery System

Husqvarna's flexible 36V system BLi-X offers battery power for everything from light and demanding homeowner tasks to professional use. One battery can be used for several tools, and the wide range of options, from lightweight integrated to backpack batteries, makes it easy to find a tailored, powerful solution that perfectly suits your task at hand. All the batteries deliver high performance, are built to be used over a long time, and can be recharged and swapped quickly for continuous use.



## **FEATURES**

- garden tasks with one tool.
- Twist the trimmer head to use the support wheel and benefit from increased control when cutting lawn edges.
- Automatic line feed with dual lines will ensure optimal trimmer line length without effort and a more even trimming result.
- Husqvarna's flexible 36V system BLi-X offers battery power for everything from light and demanding homeowner tasks to professional use.
- The product automatically shuts down when left unattended, extending battery life and reducing injury risk.

- Easily switchable attachments enabling you to carry out all common The battery is placed horizontally through the machine to reduce the risk of dirt and water getting into the battery compartment.
  - This product does not emit CO emissions during use.
  - Adjustable front handle for better control and comfortable use
  - The keypad is intuitive to operate, and you can easily adjust the settings with just the push of a button.
  - The low noise level contributes to a pleasant working environment and minimal disturbance to the surroundings.
  - Compact, lightweight design for comfortable, ergonomic use and less strain on the body.

Technical Specifications	
BATTERY	
Battery	Yes
Battery charger	40-C80
Battery pack weight	0.7 kg
Battery type	Li-lon
Battery voltage	42 V
Number of batteries included	1
Weight (excl. battery and cutting equipment)	3 kg
Weight (excl. battery)	3.2 kg
CAPACITY	-
Clutch engagement upper limit	0 rpm
Maximum power speed	6500 rpm
Maximum rpm output shaft	6500 rpm
Output shaft thread	
DIMENSIONS	
Article gross weight	5456 g
Article net weight	4857 g
Cutting width	30 cm
Tube length	1000 mm
Tube diameter	26 mm
Weight (excl. battery)	3.2 kg
ENGINE	. 3
Motor type	PMDC (2 brushed)
EQUIPMENT	1 MDC (2 brushed)
Connected digital function set (calc)	Dramium NI/A NI/A
	Premium : N/A N/A 20 °
Drive gear angle	2.8
Gear ratio Handle type	Adjustable D
Grass blade	Not included
Harness	Not included  Not included
Saw blade	Not included
Trimmer head	A15B
Output shaft thread	
PACKAGING	
	175
Packaging height	175 mm 990 mm
Packaging length Packaging volume	34.65 dm <sup>3</sup>
Packaging volume Packaging width	200 mm
Quantity in Master pack	1
MATERIALS	1
	0
Master pack: Paper material	0 g
Metal total	0 g
Paper (PAP 22) Paper material total	220 g 1270 g
HDPE (02) total	0 g
PET (01) total	0 g
Plastic foil total Plastic rigid total	90 g 0 g
Plastic rigid total	90 g
PS/EPS/HIPS (06) total	0 g
SOUND AND NOISE	o g
Sound power level, guaranteed (LWA)	00 4D(V)
Sound power level, quaranteed (LWA)	92 dB(A)
Sound power level, measured	87.6 dB(A)
Sound power level, measured Sound pressure (15m)	87.6 dB(A) 0 dB(A)
Sound power level, measured Sound pressure (15m) Sound pressure level at operators ear	87.6 dB(A)
Sound power level, measured Sound pressure (15m) Sound pressure level at operators ear VIBRATIONS	87.6 dB(A) 0 dB(A) 73.4 dB(A)
Sound power level, measured Sound pressure (15m) Sound pressure level at operators ear VIBRATIONS Daily Vibration (Aeqv)	87.6 dB(A) 0 dB(A) 73.4 dB(A) 1.36 m/s <sup>2</sup>
Sound power level, measured Sound pressure (15m) Sound pressure level at operators ear VIBRATIONS	87.6 dB(A) 0 dB(A) 73.4 dB(A)

Technical Specifications	
Equivalent vibration level (ahv, eq) front handle	1.36 m/s²
Equivalent vibration level, (ahv, eq), front handle, collapsed	1.36 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) left handle	1.36 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) rear handle	1.05 m/s <sup>2</sup>
Equivalent vibration level,(ahv, eq), rear handle, extended	1.05 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) right handle	1.05 m/s <sup>2</sup>
Vibrations handlebar	1.36 m/s <sup>2</sup>

# **ACCESSORIES**



HUSQVARNA DP110 FLXI 970 70 38-01



HUSQVARNA DE110 FLXI 970 70 40-01



BLI20 BATTERY 967 09 17-01



PREMIUM EARMUFFS WITH HEADBAND 505 66 53-04



BLI10 BATTERY 967 09 16-01



BATTERY BAG 585 37 18-01