

Husqvarna 215iL with battery and charger

Husqvarna 215iL is a battery-powered grass trimmer that is well balanced, easy to maneuver, and has the power to trim everything from lawn edges to tall grass in large gardens. The telescopic shaft is easy to adjust based on different users for good ergonomics and facilitates storage and transport. For a smooth and problem-free trimming experience, the trimmer has an intuitive keypad and a trimmer head that does not need to be taken apart when loading with a new line.

Automatic shutdown

The product automatically shuts down when left unattended, extending battery life and reducing injury risk.

Efficient Brushless Motor

Brushless motor for higher efficiency, longer lifetime, and less maintenance compared to brushed motors. Since there are no brushes, friction is eliminated, no energy is lost, and the motor runs cooler. This also eliminates the need for maintenance or replacement of worn brushes, and you can benefit from improved performance and higher torque.

Low Carbon Emissions

By choosing this product, you can feel confident that it produces lower carbon emissions during active use compared to a traditional petrol product. This battery-driven product does not emit any CO during use while still providing the power and quality that you expect from a Husqvarna product. However, it's important to note that CO emissions are generated during other stages of the product's lifecycle, such as production, charging and endof-life disposal.



Power-Conserving savE™ Mode

SavE[™] mode maximises the run time, reduces noise levels and preserves product battery life by lowering the rpm. Ideal for tasks that do not require full power. Just press the button to turn savE[™] mode on and off.

FEATURES

- This product does not emit CO emissions during use.
- Brushless motor for higher efficiency, longer lifetime and less maintenance compared to brushed motors.
- The product automatically shuts down when left unattended, extending battery life and reducing injury risk.
- SavE[™] mode maximises the run time by lowering the rpm and is ideal for tasks that do not require full power.
- Husqvarna's flexible 36V system BLi-X offers battery power for everything from light and demanding homeowner tasks to professional use.
- The low noise level contributes to a pleasant working environment and minimal disturbance to the surroundings.
- The battery is placed horizontally through the machine to reduce the risk of dirt and water getting into the battery compartment.
- With the Rapid Replace[™] trimmer head, you can easily reload the trimmer line without opening the cover.
- Compact, lightweight design for comfortable, ergonomic use and less strain on the body.
- The keypad is intuitive to operate, and you can easily adjust the settings with just the push of a button.

BATRYVesBathyryck wap949Bathyryck wap969Bathyryck wap969Bathyryck wap969Bathyryck wap100Bathyryck wap100Namba of antyrych wap100Namba of antyrych wap261Wapit (act lathyr, dama of antyrych wap	Technical Specifications	
	BATTERY	
	Battery	Yes
Bether yopUse has instance instance i	· · · · · · · · · · · · · · · · · · ·	
Bethery hereUnder control of the second of the		
Battery visage40 VBattery visage1Wagter (ext Latitary and culling acupment)28 logWagter (ext Latitary and culling acupment)28 logWagter (ext Latitary and culling acupment)28 logWagter (ext Latitary and culling acupment)6600 rpmMammur promoter speed6600 rpmMammur promoter speed6600 rpmMarter promoter speed7Wagter (ext Latitary acupment)42 rpmWagter (ext Latitary acupment)42 rpmMarter promoter speed31 rpmArchor gross wagter42 rpmArchor gross wagter24 rpmWagter (ext Latitary acupment)20 rpm <td< td=""><td></td><td>~</td></td<>		~
Number picture1Weight (dot battery out outing agament)26 kgWeight (dot battery out outing agament)26 kgCARACTYMarram promotyper dath6800 pmCarpot after frad6800 pmCarpot after frad6800 pmCarpot after frad270 gCarpot after frad270 gArcise per sweight270 gArcise per sweight270 gCating work1040 mmCating work1040 mmCating work1040 mmTake arces per sweight29 kgCating work29 kgCating work29 kgCating work29 kgCating work29 kgCating work20 kgCating work		
Weight (etc. bankey and ading suppored)26 kgVersite (etc. bankey and ading suppored)29 kgCAPACIYCAPACIYMainsma proor speed600 pmMainsma proor speed600 pmMainsma proor speed-DMESSIONArtick gross weight4230 gArtick gross weight3700 gArtick gross weight </td <td></td> <td></td>		
Weight (ack battery)29 lg algMeanur proceuded bath6800 pmCarbon (Comparing the Act of Comparing the Act of		
CARCNYendMaximu prorupted balt600 pmMaximu prorupted balt600 pmMaximu prorupted balt600 pmData Salt Proceed balt700 pmDirection proceed balt220 pmDirection proceed balt220 pmDirection proceed balt220 pmDirection proceed balt220 pmDirection proceed balt240 pmDirection proceed balt250 pmDirection proceed		
Marrar ngn opers speed6800 gmAuge shall fread6800 gmOutpet shall freadDMENSIONSAfteds gmas weight4230 gAfteds gmas weight31 cmIbbe speed31 cmIbbe speed24 mmWeight (act basis)24 mmIbbe speed24 mmWeight (act basis)24 mmWeight (act basis)0 *Ger stop1After speed1000Arras basisNot relatedWeight (act basis)1000Arras basisNot relatedHarras SNot relatedTormar bad2520Cupt shall freed20 mmParkagning height152 mmParkagning height152 mmParkagning height20 mmParkagning weitine20 mmParka		2.9 kg
Marton pro adjad shaft6800 spmOptig shaft freedDMESDNSArtisk porswalph3790 gArtisk porswalph3790 gCatting vach1040 nmLoke langh1040 nmCatting vach1040 nmLoke langh1040 nmLoke langh29 langWaght (ext Loke langh29 langNoght (ext Loke langh29 langENDE <td>CAPACITY</td> <td></td>	CAPACITY	
Output shaft mead		6800 rpm
Output shaft mead	Maximum rpm output shaft	6800 rpm
Artice pres weight 4230 g Artice net weight 31 cm Line weight 31 cm Line weight 31 cm Line weight 24 mm Line weight 24 mm Line duration 24 mm Weight (exc) bartery) 29 kg EXINE EXINE Motor type BDC (trusthess) EQUIPMENT 0° Cases thate 0° Gases thate 0° Gases thate Not related and and and and and and and and and an		
Artice pres weight 4230 g Artice net weight 31 cm Line weight 31 cm Line weight 31 cm Line weight 24 mm Line weight 24 mm Line duration 24 mm Weight (exc) bartery) 29 kg EXINE EXINE Motor type BDC (trusthess) EQUIPMENT 0° Cases thate 0° Gases thate 0° Gases thate Not related and and and and and and and and and an	DIMENSIONS	
Atcle revended3720 gAtcle revended31 cmTube length1040 mmTube length24 mmWeight (act battery)29 kgENGNEDC (trusthess)ENGNEDC (trusthess)EQUIPENTEDC (trusthess)Casa trado0°Casa trado1Hendle type0°Casas tradoNot includedHendle type1Casa tradoNot includedHendle type20%Casas tradoNot includedHendle type152 mmPassagn forsignt152 mmPassagn forsignt200 mmCasaster pack0Passagn forsignt0Natter pack type material0Natter pack type mate		4020 a
Cutting with31 cmCutting with31 cmTube length34 cmTube length24 mmWeight (act tuber)29 legENGNE50 cm/sthes)EUUPHENT0°Cutting length0°Bar ratio0°Far ratio1Hende type00 pmGrass bladkNot includedHarnesNot includedTermmer head2528Cutting length2528Cutting length2528Cutting length2528Cutting length2528Cutting length152 mmPackagn freight152 mmPackagn freight35 dm ³ Packagn with350 dm ³ Cass tubid00 pmPackagn with30 dm ³ Packagn with30 dm ³ Packagn with0Packagn with0Cass tubid0Packagn with0Packagn with0 <td< td=""><td></td><td></td></td<>		
Tube Sample1040 mmWeight (act batary)29 kgENCIN29 kgENCINENCINEQUIPACINABUC (trustless)EQUIPACINA0*Corr top0*Corr top0*Corr top0*Corr top0*Corr top0*Corr top0*Corr top0*Corr top0*Corr top0*Corr top1Handle type0*Corr top1Handle type10Corr top10Fandle type10Corr top26.96Corr top12.96Corr top26.96Corr top12.97Packargin top00.97Packargin top0.9Packargin top0.9<		
Tube dimeter 24 mm Weight (excl. battery) 29 kg ExcNic 29 kg Moter type BCC (trusthess) Butter part angle 0* Gear ando 1 Indea type Loop Gear ando 0* Gear ando 0* Gear ando 1 Indea type Loop Grass Bide Not included Markers Not included Timmer head 6258 Output Staff tread ** Packaging height 1250 mm Packaging voluma 38 dm* Packaging voluma 200 mm Quantity in Master pack 1 Master pack Paper material 0g		
Weight (scit battery)29 kgENGINEKotter typeBDC (brushless)EQUIPMENT0°Constration1Handle typeLoopclass bladeNot includedHandle typeNot includedClass bladeNot includedHarnesNot includedHarnesP258Curput shaft threadP258Curput shaft thread1250 mmPackaging leight152 mmPackaging leight152 mmPackaging volume38 dm³Packaging volume200 mmPackaging volume0 gPackaging volume0 g <td< td=""><td></td><td></td></td<>		
ENNIMEMotor typeBDC (bushless)BUTIPHENTBDC (bushless)Drive gar angle0°Gear ratio0°Handle type000Grass bladgeNot includedHandle typeNot includedHandle typeNot includedGrass bladgeNot includedHandle type258Output staft thread258Packaging length152 mmPackaging length152 mmPackaging length200 mmPackaging volume200 mmPackaging volume200 mmPackaging volume200 mmPackaging volume38 dm ³ Packaging volume00 mmPackaging volume00 mm<		
Motor type BLDC (brushless) EQUIPMENT Drive gas ranjle 0* Gear ratio 1 Handle type Loop Grass blade Not included Harnels type Not included Timmer hadd R25B Output shaft thread R25B Packaging height 152 mm Packaging height 1250 mm Packaging volume 38 dm ³ Packaging volume 30 dm ³ Packaging volume 0 g Master pack Paper material 0 g Master pack Paper material 0 g Master pack Paper material 0 g Paper (PAP 22) 0 g Paster cipit fold 0 g Paper (PAP 22) 0 g Paper (PAP 22) 0 g Paster cipit fold 0 g Paster cipit fold 0 g <	Weight (excl. battery)	2.9 kg
EQUIPMENTO*Drive gear angle0*Gear ratio1Handle typeLoopVarian StadeNot includedHannessNot includedHarnessNot includedTimmer headR256Output staft threadPACKaliNKPackaging height1250 mmPackaging use38 dm³Packaging volume38 dm³Packaging volume38 dm³Packaging volume00 mmPackaging volume00 gmPackaging volume0 gPackaging volume0 gPack Volume0 gPack Volume0	ENGINE	
EQUIPMENTO*Drive gear angle0*Gear ratio1Handle typeLoopVarian StadeNot includedHannessNot includedHarnessNot includedTimmer headR256Output staft threadPACKaliNKPackaging height1250 mmPackaging use38 dm³Packaging volume38 dm³Packaging volume38 dm³Packaging volume00 mmPackaging volume00 gmPackaging volume0 gPackaging volume0 gPack Volume0 gPack Volume0	Motor type	BLDC (brushless)
Drive gear angle0 °Gear ratio1Cara ratio1Hancle typeLoopGrass bladeNot includedHarnessNot includedTrimmer headR258Culput shaft thread~Packaging height152 nmPackaging height152 nmPackaging yolume38 dm³Packaging yolume38 dm³Packaging with200 nmQuantity in Master pack1Master pack Reper material0 gMaster pack Reper material0 gOther basic rigid0 gPastic rigid total0 gSound power level measured (WA)92 dd(A)Sound power lev		
Gear ratio 1 Handle type Loop Grass tade Not included Harness Not included Trimmer head R258 Cutput shaft thread ~ Packaging length 152 mm Packaging length 152 mm Packaging length 152 mm Packaging upth 1250 mm Packaging upth 200 mm Packaging with 200 mm Open state pack 200 mm Master pack Paper material 0g Master pack Paper material 0g Other plastic rigid 0g Paper material total 0170 g Other plastic rigid 0g Paper material total 0g PAPE (22) total 0g Paper material total 0g Paper material total 0g Pastic foid 0g Pastic foid 0g Pastic foid 0g Paper material total 0g Paper material total 0g Pastic foid 0g Pastic foid total		
Handle typeLoopGrass tiladeNot includedHarnessNot includedTimmer headR258Cutput shaft thread~Packaging height152 mmPackaging height1520 mmPackaging not thread38 dm³Packaging not thread200 mmPackaging with200 mmQuantity in Master pack1MATERIALS1MATERIALS0 gOther paster rigid0 gPackaging clude0 gPackaging clude0 gPackaging clude0 gPackaging clude0 gMATERIALS0 gOther paster rigid0 gPackaging clude0 gPaster clude <td></td> <td></td>		
Grass Badie Not included Harness Not included Trimmer head R25B Output shaft thread ~ PackAging height 152 mm Packaging ungth 152 mm Packaging voltme 38 dm³ Packaging voltme 38 dm³ Packaging voltme 00 pm Quantity in Master pack 1 Matter pack 0 g Matter pack Paper material 0 g Motion Coll 0 g Other pastic rigid 0 g Op 0 g Pack Coll 0 g Pack Total 0 g Pastic fold 0 g PEC (0) total 0 g Pastic fold total 0 g Sound power level quaranteed (UWA) 92 dB(A) Sound power level quaranteed (UWA) 92 dB(A) Sound power level quaranteed (WA) 92 dB(A) Sound power level quaranteed (WA) 92 dB(A) Sound power level quaranteed (WA) 92 dB(A) S		
Harness Not included Trimme head R258 Output shaft thread ~ PAcKaQING ~ Packaging height 152 mm Packaging length 1520 mm Packaging use 38 dm³ Packaging use 38 dm³ Packaging use 00 mm Oxantity in Master pack 1 Master pack Paper material 0 g Master pack Paper material 0 g Master pack Paper material 0 g Paper (PAP 22) 0 g Of the pastic: rigid 0 g Paster pack Paper material total 1170 g HOPE (O2) total 0 g Paster pack (Paper material total 0 g Paper (PAP 22) 0 g Paper (PAP 22) 0 g Paster pack (Paper material total 0 g HOPE (O2) total 0 g Paster total total 0 g Sound power level, guaranteed (LWA) 92 dB(A) <t< td=""><td></td><td></td></t<>		
Timmer head R25B Otgut shaft thread PackAging height 152 mm Packaging length 152 mm Packaging volume 38 dm ³ Packaging volume 0 g Master pack 1 Master pack 0 g Master pack Paper material 0 g Master pack Paper material 0 g Other plastic rigid 0 Opper (PAP 22) 0 g Opper (PAP 22) 0 g Paper (PAP 22) 0 g Sound power level (ball 0 g Paper (PAP	Grass blade	
Output shaft thread	Harness	Not included
PACKAGING Image: Second S	Trimmer head	R25B
Packaging height152 mmPackaging length1250 mmPackaging volume38 dm³Packaging volume200 mmPackaging width200 mmQuantity in Master pack1MATERIALS0 gMatter pack Paper material0 gMater pack Paper material0 gMater pack Paper (PAP 22)0 gPaper (PAP 22)0 gPaper (PAP 22)0 gPaper material total1170 gHDPE (O2) total0 gPlastic rigid Total0 gPastic toti total0 gSOUND AND NOISE0 gSound power level, masured905 dB(A)Sound pressure (15m)0 dB(A)Sound pressure (15m)0 dB(A)Sound pressure (15m)0 dB(A)Sound pressure (AS)45 m/s²Daily Vibration (Acqv)45 m/s²Daily Vibration (Acqv)0 3hDaily Vibration Irue (Time factor)0 3hEquivalent Vibration Irue (Time factor)0 3hEquivalent Vibration Irue (Time factor)0 3h	Output shaft thread	
Packaging height152 mmPackaging length1250 mmPackaging volume38 dm³Packaging volume200 mmPackaging width200 mmQuantity in Master pack1MATERIALS0 gMatter pack Paper material0 gMater pack Paper material0 gMater pack Paper (PAP 22)0 gPaper (PAP 22)0 gPaper (PAP 22)0 gPaper material total1170 gHDPE (O2) total0 gPlastic rigid Total0 gPastic toti total0 gSOUND AND NOISE0 gSound power level, masured905 dB(A)Sound pressure (15m)0 dB(A)Sound pressure (15m)0 dB(A)Sound pressure (15m)0 dB(A)Sound pressure (AS)45 m/s²Daily Vibration (Acqv)45 m/s²Daily Vibration (Acqv)0 3hDaily Vibration Irue (Time factor)0 3hEquivalent Vibration Irue (Time factor)0 3hEquivalent Vibration Irue (Time factor)0 3h	PACKAGING	
Packaging length 1250 mm Packaging volume 38 dm³ Packaging volume 200 mm Quantity in Master pack 1 MATERIALS 0g Master pack Paper material 0g Master pack Paper material 0g Other plastic rigid 0g Parper (PAP 22) 0g Paper material total 1170 g HDPE (02) total 0g Pastic foil total 0g Pastic foil total 0g Pastic total 0g Sound power level quaranteed (UWA) 0g Sound pore revel quaranteed (UWA) 92 dB(A) Sound pressure level at operators ear 74 9 dB(A) Sound pressure level at operators ear 74 9 dB(A) Sound pressure (15m) 0dB(A) Sound pressure (AB) 45 m/s² Daily Vibration Revg(AV) 45 m/s² Daily Vibration Inere (Time factor) 03 h Equivalent Vibration Inere (Time factor) 03 h		152 mm
Packaging volume 38 dm³ Packaging width 200 mm Quantity in Master pack 1 Matterials 0 Master pack Paper material 0 g Matterials 0 Other plastic rigid 0 Paper (PAP 22) 0 g Paper (PAP 22) 0 g Paper (PAP 22) 0 g Paper (DAP 20) 0 g Paper (DAP 20) 0 g		
Packaging width 200 mm Quantity in Master pack 1 MATERIALS 0g Matter pack Paper material 0g Mater totak 0g Metal total 0g Other plastic rigid 0g Paper (PAP 22) 0g Paper material total 1170 g HDPE (02) total 0g PET (01) total 0g Pastic rigid total 0g Pastic foid total 0g Plastic rigid total 0g Pastic foid total 0g Pastic foid total 0g Pastic foid total 0g PstrE (50) total 0g Sound power level guaranteed (LWA) 92 dB(A) Sound power level apperators ear 74.9 dB(A) Sound pressure level at operators ear 74.9 dB(A) Daily Vibration (Aeqv) 45 m/s ² Daily Vibration Time (Time factor) 0.3 h Equivalent Vibration Time (Time factor) 0.3 h		
Quantity in Master pack 1 MATERIALS 0g Master pack. Paper material 0g Metal total 0g Other plastic: rigid 0 Paper material total 1170 g HDPE (02) total 0g Paper material total 0g Plastic rigid total 0g Sound power level, guaranteed (LWA) 0g Sound power level, measured 90.5 dB(A) Sound pressure level at operators ear 74.9 dB(A) Vibration (Aeqv) 45 m/s² Daily Vibration (Aeqv) 45 m/s² Daily Vibration Time (Time factor) 03 h Equivalent vibration level (ahv. eq) front handle 45 m/s²		
MATERIALSMaster pack: Paper material0 gMetal total0 gOther plastic: rigid0Paper (PAP 22)0 gPaper material total1170 gHDPE (02) total0 gPET (01) total0 gPlastic rigid total0 gPastic rigid total0 gSound power level, guaranteed (LWA)0 gSound pressure (LWA)92 dB(A)Sound pressure level at operators ear74 3 dB(A)VIBRATIONS74 3 dB(A)Daily Vibration (Aeqv)45 m/s²Daily Vibration Time (Time factor)0.3 hEquivalent vibration level (ave, eq) front handle0.3 h		
Master pack: Paper materialO gMetal totalO gOther plastic: rigidOPaper (PAP 22)O gPaper material total1170 gHDPE (02) totalO gPET (01) totalO gPlastic rigid totalO gSound power level, guaranteed (LWA)O g BSound power level, measuredO g BSound power level at operators ear74.9 dB(A)ViBRATIONSDally Vibration Exposure (A8)Daily Vibration Exposure (A8)0.3 hDaily Vibration Exposure (A8)0.3 hEquivalent vibration level (anve, q) front handle0.3 h		1
Metal total 0 g Other plastic rigid 0 Paper (PAP 22) 0 g Paper material total 1170 g HDPE (02) total 0 g PET (01) total 0 g Plastic foli total 0 g SOUND AND NOISE 0 g Sound power level, quaranteed (LWA) 9 2 dB(A) Sound power level, measured 90.5 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS T Daily Vibration (Aeqv) 45 m/s² Daily Vibration Exposure (A8) 0.3 h Daily Vibration Exposure (A8) 0.3 h Equivalent vibration level (ave, eq) front handle 45 m/s²	MATERIALS	
Metal total 0 g Other plastic rigid 0 Paper (PAP 22) 0 g Paper material total 1170 g HDPE (02) total 0 g PET (01) total 0 g Plastic foli total 0 g SOUND AND NOISE 0 g Sound power level, quaranteed (LWA) 9 2 dB(A) Sound power level, measured 90.5 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS T Daily Vibration (Aeqv) 45 m/s² Daily Vibration Exposure (A8) 0.3 h Daily Vibration Exposure (A8) 0.3 h Equivalent vibration level (ave, eq) front handle 45 m/s²	Master pack: Paper material	0 g
Other plastic: rigid O Paper (PAP 22) 0 g Paper material total 1170 g HDPE (02) total 0 g PET (01) total 0 g Plastic foil total 0 g Sound power level, quaranteed (LWA) 0 g Sound power level, quaranteed (LWA) 92 dB(A) Sound power level a toperators ear 74.9 dB(A) VIBRATIONS T Daily Vibration (Aeqv) 45 m/s² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (abv, eq) front handle 45 m/s²	Metal total	0 g
Paper (PAP 22) O g Paper material total 1170 g HDPE (02) total O g PET (01) total O g Plastic foil total O g Plastic foil total O g Plastic foil total O g PS/EPS/HIPS (06) total O g Sound power level, guaranteed (LWA) O g Sound power level, guaranteed (LWA) 92 dB(A) Sound power level at operators ear 74.9 dB(A) VIBRATIONS Daily Vibration Exposure (A8) 4.5 m/s² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (aiv, eq) front handle 4.5 m/s²	Other plastic: rigid	
Paper material total1170 gHDPE (O2) total0 gPET (O1) total0 gPlastic foil total0 gPlastic foil total0 gPlastic total0 gPlastic total0 gPS/EPS/HIPS (06) total0 gSound power level, guaranteed (LWA)92 dB(A)Sound power level, measured90.5 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear74.9 dB(A)VIBRATIONSJDaily Vibration (Aeqv)4.5 m/s²Daily Vibration Time (Time factor)0.3 hEquivalent vibration level (ahv, eq) front handle4.5 m/s²		
HDPE (02) total0 gPET (01) total0 gPlastic foil total0 gPlastic rigid total0 gPlastic rigid total0 gPlastic total0 gPlastic total0 gSound power level, guaranteed (LWA)92 dB(A)Sound power level, guaranteed (LWA)92 dB(A)Sound power level, measured90 sd dB(A)Sound pressure level at operators ear74.9 dB(A)VIBRATIONS1Daily Vibration (Aeqv)45 m/s²Daily Vibration Time (Time factor)0.3 hEquivalent vibration level (ahv, eq) front handle45 m/s²		
PET (01) total0 gPlastic foil total0 gPlastic rigid total0 gPlastic rigid total0 gPlastic total0 gPlastic total0 gSOUND AND NOISE0 gSound power level, guaranteed (LWA)92 dB(A)Sound power level, measured90.5 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear74.9 dB(A)VIBRATIONS1Daily Vibration (Aeqv)4.5 m/s²Daily Vibration Time (Time factor)0.3 hEquivalent vibration level (ahv, eq) front handle4.5 m/s²		•
Plastic foil total0 gPlastic rigid total0 gPlastic rigid total0 gPlastic total0 gPs/EPS/HIPS (06) total0 gSOUND AND NOISE0Sound power level, guaranteed (LWA)92 dB(A)Sound power level, measured90.5 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear74.9 dB(A)VIBRATIONS2Daily Vibration (Aeqv)4.5 m/s²Daily Vibration Time (Time factor)0.3 hEquivalent vibration level (ahv, eq) front handle4.5 m/s²		
Plastic rigid total 0 g Plastic total 0 g Ps/EPS/HIPS (06) total 0 g SOUND AND NOISE 0 g Sound power level, guaranteed (LWA) 92 dB(A) Sound power level, measured 90.5 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS Daily Vibration (Aeqv) Daily Vibration Exposure (A8) 45 m/s² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (ahv, eq) front handle 45 m/s²		
Plastic total 0 g PS/EPS/HIPS (06) total 0 g SOUND AND NOISE 92 dB(A) Sound power level, guaranteed (LWA) 92 dB(A) Sound power level, measured 90.5 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS 1 Daily Vibration (Aeqv) 4.5 m/s² Daily Vibration Exposure (A8) 4.5 m/s² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (ahv, eq) front handle 4.5 m/s²		
PS/EPS/HIPS (06) total 0 g SOUND AND NOISE 92 dB(A) Sound power level, guaranteed (LWA) 92 dB(A) Sound power level, measured 90.5 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS 1 Daily Vibration (Aeqv) 4.5 m/s² Daily Vibration Exposure (A8) 4.5 m/s² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (ahv, eq) front handle 4.5 m/s²		·
SOUND AND NOISESound power level, guaranteed (LWA)92 dB(A)Sound power level, measured90.5 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear74.9 dB(A)VIBRATIONS		
Sound power level, guaranteed (LWA)92 dB(A)Sound power level, measured90.5 dB(A)Sound pressure (15m)0 dB(A)Sound pressure level at operators ear74.9 dB(A)VIBRATIONS		Og
Sound power level, measured 90.5 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS 4.5 m/s² Daily Vibration (Aeqv) 4.5 m/s² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (ahv, eq) front handle 4.5 m/s²	SOUND AND NOISE	
Sound power level, measured 90.5 dB(A) Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS 4.5 m/s² Daily Vibration (Aeqv) 4.5 m/s² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (ahv, eq) front handle 4.5 m/s²	Sound power level, guaranteed (LWA)	92 dB(A)
Sound pressure (15m) 0 dB(A) Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS		
Sound pressure level at operators ear 74.9 dB(A) VIBRATIONS		
VIBRATIONS 4.5 m/s² Daily Vibration (Aeqv) 4.5 m/s² Daily Vibration Exposure (A8) 4.5 m/s² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (ahv, eq) front handle 4.5 m/s²	55616 prosses (1511)	
Daily Vibration (Aeqv)4.5 m/s²Daily Vibration Exposure (A8)4.5 m/s²Daily Vibration Time (Time factor)0.3 hEquivalent vibration level (ahv, eq) front handle4.5 m/s²		
Daily Vibration Exposure (A8) 4.5 m/s ² Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (ahv, eq) front handle 4.5 m/s ²	Sound pressure level at operators ear	/4.9 dB(A)
Daily Vibration Time (Time factor) 0.3 h Equivalent vibration level (ahv, eq) front handle 4.5 m/s ²	Sound pressure level at operators ear VIBRATIONS	
Equivalent vibration level (ahv. eq) front handle 4.5 m/s ²	Sound pressure level at operators ear VIBRATIONS Daily Vibration (Aeqv)	4.5 m/s ²
	Sound pressure level at operators ear VIBRATIONS Daily Vibration (Aeqv) Daily Vibration Exposure (A8)	4.5 m/s ² 4.5 m/s ²
Equivalent vibration level (ahv, eq), front handle, collapsed 4.5 m/s ²	Sound pressure level at operators ear VIBRATIONS Daily Vibration (Aeqv) Daily Vibration Exposure (A8) Daily Vibration Time (Time factor)	4.5 m/s ² 4.5 m/s ² 0.3 h
	Sound pressure level at operators ear VIBRATIONS Daily Vibration (Aeqv) Daily Vibration Exposure (A8) Daily Vibration Time (Time factor)	4.5 m/s ² 4.5 m/s ² 0.3 h

Technical Specifications	
Equivalent vibration level (ahv, eq) left handle	0 m/s ²
Equivalent vibration level (ahv, eq) rear handle	2.7 m/s ²
Equivalent vibration level.(ahv, eq), rear handle, extended	2.7 m/s ²
Equivalent vibration level (ahv, eq) right handle	0 m/s ²
Vibrations handlebar	0 m/s ²