

Husqvarna 120iTK4-P without battery and charger

Husqvarna 120iTK4-P – a battery-powered pole saw that delivers petrol performance combined with a low noise level. It comes with a pole saw attachment but can also be combined with a hedge trimmer attachment, making the 120iTK4-P a versatile tool that can be used for both hedge trimming and cutting branches. Equipped with a telescopic tube with up to 4 m reach and a split shaft that facilitates transport.



Power-Conserving savE™ Mode

SavE[™] mode maximises the run time, reduces noise levels and preserves product battery life by lowering the rpm. Ideal for tasks that do not require full power. Just press the button to turn savE[™] mode on and off.

Low Carbon Emissions

By choosing this product, you can feel confident that it produces lower carbon emissions during active use compared to a traditional petrol product. This battery-driven product does not emit any CO during use while still providing the power and quality that you expect from a Husqvarna product. However, it's important to note that CO emissions are generated during other stages of the product's lifecycle, such as production, charging and endof-life disposal.



Quiet operation

The low noise level contributes to a pleasant working environment and minimal disturbance to the surroundings.

Transport mode

The product can be split in half without using tools, for easy transportation and storage.



FEATURES

- SavE[™] mode maximises the run time by lowering the rpm and is ideal for tasks that do not require full power.
- The low noise level contributes to a pleasant working environment and minimal disturbance to the surroundings.
- This product does not emit CO emissions during use.
- The product can be split in half without using tools, for easy transportation and storage.
- Telescopic tube for quick cutting height adjustment makes it convenient to adapt to different tasks.
- The product automatically shuts down when left unattended, extending battery life and reducing injury risk.
- Husqvarna's flexible 36V system BLi-X offers battery power for everything from light and demanding homeowner tasks to professional use.
- Compact, lightweight design for comfortable, ergonomic use and less strain on the body.
- Quick and easy chain tensioning and assembling of the bar and the chain without using any tools.

BATESYNoBIRDY YORNoBIRDY YOR-BIRDY YOR-BIRDY YOR-CAROLTY- <th>InstanceNoBattery ope2.0 AhBattery type-Battery type-Charped arms power0.0 m/sCitipang capacity max0.0 m/sCitipang capacity max0.0 m/sMinistro data0.0 m/sMinistro data0.0 m/sCitipang capacity max0.0 m/sAncing pass anglit60.0 gAncing pass anglit0.0 m/sAncing pass anglit0.0 m/sAncing pass anglit0.0 m/sAncing pass anglit0.0 m/sCitipang capacity max0.0 m/sSite0.0 m/sCitipang capacity max0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sConnected data function set (abc)1.0 m/sFight0.0 m/sConnected data function set (abc)1.0 m/sFisher0.0 m/sConnected data function set (abc)1.0 m/sFisher0.0 m/sSite0.0 m/sConnected data function set (abc)1.0 m/sFisher0.0 m/sSite0.0 m/sConnected data function set (abc)0.0 m/sFisher0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite</th> <th>Technical Specifications</th> <th></th>	InstanceNoBattery ope2.0 AhBattery type-Battery type-Charped arms power0.0 m/sCitipang capacity max0.0 m/sCitipang capacity max0.0 m/sMinistro data0.0 m/sMinistro data0.0 m/sCitipang capacity max0.0 m/sAncing pass anglit60.0 gAncing pass anglit0.0 m/sAncing pass anglit0.0 m/sAncing pass anglit0.0 m/sAncing pass anglit0.0 m/sCitipang capacity max0.0 m/sSite0.0 m/sCitipang capacity max0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sConnected data function set (abc)1.0 m/sFight0.0 m/sConnected data function set (abc)1.0 m/sFisher0.0 m/sConnected data function set (abc)1.0 m/sFisher0.0 m/sSite0.0 m/sConnected data function set (abc)1.0 m/sFisher0.0 m/sSite0.0 m/sConnected data function set (abc)0.0 m/sFisher0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite0.0 m/sSite	Technical Specifications	
<table-row><table-row><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-row></table-row>	Interpretation2.0.hBattery close	BATTERY	
<table-row><table-row><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-row></table-row>	Interpretation2.0.hBattery close	Battery	No
Ballery (rigned	Jesting volge-CAPACITY-CAPACITY-Carlangeed trace poor30 m/ACarlangeed trace poor30 m/ACarlangeed trace poor500 nArticle of exergin500 nArticle of exergin500 nCarlangeed trace poor30 an CDer kergin500 nCarlangeed trace poor30 an CSee30 an CSee30 an CSee30 an CSee30 an CSee30 an CSee30 an CSee35 sinTabe length30 an CSee35 sinTabe length35 sinWeight (col stating exagement)35 sinCarlange exagement	Battery capacity	2.0 Ah
Batery votageSelfChar prograde trans poer10 m/sDurphy capacity max5 m/mDirphy capacity max5000 m/mDirphy capacity max5000 m/mDirphy capacity max5000 m/mDirphy capacity max5000 m/mDir dire bit wegit5000 m/mDir dire bit wegit304 cmDir dire bit wegit305 cmWegit (well bit wegit weg	Battery voltage36 VCAPACITYIn m6Chait speed at mac scorer10 m6O punc speed (max5 m1/m1OMESIONSFArtisle grass weight6600 gArtisle grass weight6000 gArtisle grass weight500 ngFall weight pucktafts pating engineert33 do enSie10Lobe darsder30 do enSie10Lobe darsder30 do enSie100 mnWeight (did scattery and cating equipment)355 ligWeight (did scattery and cating equipment)355 ligStare SiePMCC (2 travine)EQUENTN100Connected data later and scatter and scat		
CAPACITY	CAPACTYUChirsi speed into speed.10 m/sChirsi speed into speed.500 qMikkle gross neight.500 qAffer ferdingt.500 qAffer ferdingt.500 qAffer ferdingt.500 qFaller grom.500 qAffer ferdingt.500 qAffer ferdingt.55 figAffer ferdingt.55 figAffer ferdingt.55 figAffer ferdingt.55 figAffer ferdingt.700 qAffer ferdingt.700 q		36 V
Otherwise5ml/minOtherwise6000 gAnticing press weight6000 gAnticing press weight6000 gAnticing press weight500 gAnticing press weight600 gAnticing press weight600 gConnected digital function on (cat)Margenicality and comp press press Tool :WANAPich144 GConnected digital function on (cat)Margenicality and comp press press Tool :WANAPich144 GConnected digital function on (cat)Margenicality and comp press press Tool :WANAPich144 GStorder type500 gConnected digital function on (cat)Margenicality and comp press	Of pump search maxSml/mOf pump search maxSconArrice grass weightStol 0Rain early mightStol 0Rain early mightStol 0Rain early mightStol 0Rain early mightStol 0StareIDTube denoterStormStareStormTube denoterStormTube denoterStormTube denoterStormTube denoterStormTube denoterStormTube denoterStormTube denoterStormTube denoterStormTube denoterStormTube denoterStormRestrict for a stormStormRestrict for a stormStorm </td <td></td> <td></td>		
Olipung papek maSm/maOlipung papek masSm/maArking may mg/hSm00 qArking may mg/hSm00 qBar langhSm10 qFall sign including cuting equipment (Sm10 qSmSm10 qTuo darmafarSm10 qWagn (sci cuting cuting equipment)Sm10 qWagn (sci cuting equipment)Sm10 qWagn (sci cuting equipment)Sm10 qSm10 qMarga Cuting aquipmentSm10 qMa	Oppung spach/naxSml/minOppung spach/naxSml/minArrice grass weightSt000 gArrice grass weightSt000 gArrice grass weightSt000 gBar kerghnSt000 gBar kerghnSt000 gArrice grass weightSt000 gBar kerghnSt000 mmStateI0Tube forght incluous outne sequencesSt55 gBreak regist (sect barber and cutting outnemet)St55 gBreak regist (sect barber and cutting outn	Chain speed at max power	10 m/s
DMMSNONS	DMMSNMS9000000000000000000000000000000000000		5 ml/min
Anche ner weight6600 gAnche ner weight600 gBer length25 cmDer length including outing equipment384 cmStre10Dar length including outing equipment356 lgWeight end outing equipment356 lgWeight end outing equipment)356 lgWeight end outing equipment356 lgCommeted digital function set (saf)PMC1 (2 bushed)Phot144Serootal typeNatagelabaeCommeted digital function set (saf)NatagelabaeUBRCANSSerootal typeOuting typeSerootal typeOuting typeSe	Article net sergit 5000 g Riv Incych 5100 g Riv Incych 30 d cm Dial sergit Article and sergit 30 d cm Sage 10 Lide deneter 35 mm Lide deneter 35 mm Lide deneter 35 mm Lide deneter 355 log Weight (ect colling equipment) 355 log Weight (ect colling equipment) 355 log ENCM Hot Connected digital function set (calc) Hot Pitch Hot Connected digital function set (calc) Hot Pitch J44 Strocker type Strocker type Connected digital function set (calc) Not applicable UBRICHARTS UBRICHARTS UBRICHARTS Strocker type Mater pack Paper motion 0g1 Mater pack Paper motion 0g1 Mater pack Paper motion 0g Mater pack Paper motion 0g Mater pack Paper motion 0g Mater pack Paper motion 0g <		
Artok newspit510 g 1Artok newspit304 cmSar length304 cmSar length304 cmSar length307 cmTable agent newspit355 sgWeight (act atting equipment)355 sgWeight (act atting equipment)400 rmWeight (act atting equipment)400 rmConsetted digit function set (act)400 rmConnected digit function set (act)5 gurConnected digit function set (act)800 rmPitch1/4Pitch1/4Pitch1/4Pitch1/4Pitch1/4Pitch1/4Pitch001Connected digit function set (act)800 rmPitch1/4Pitch	Antce reweight500 gFail neight, niculing eaupment26 mSee10Tubb ength, niculing eaupment35 fungUbbe length1900 mmWeight (edic soluting eaupment)355 fugWeight (edic soluting eaupment)355 fugWeight (edic soluting eaupment)355 fugWeight (edic soluting eaupment)355 fugCharting fug1000 cmWeight (edic soluting eaupment)1000 cmCharting fug1000 cmCharting fug1000 cmConnected digit function set (cak)Hussen Common Service Tool: NA NAPath1/44Stroker fugSignolatingConnected digit function set (cak)Nut applicateUbber fugSignolatingConnected digit function set (cak)SignolatingPath1/44Stroker fugSignolatingConnected vig fugSignolatingConnected vig fugSignolatingConnected vig fugSignolatingConnected vig fugSignolatingMatter fusSignolatingMatter fusSignolating <trr>Matter fusS</trr>		6600 g
Bar length25 cm25 cmBar length30 cmSize10Faile length inclust outing equipment35 form (Use length1900 mmWeight (end cutting equipment)355 hqWeight (end cutting equipment)400Connected digital function set (calc)HuPart (Part hg900Weight (end cutting equipment)1/4"Weight (end cutting equipment)001Weight (end cutting equipment)01Weight (end cutting equipment)01Weight (end cutting equipment)01Weight (end cutting equipment)1/4"Weight (end cutting equipment)1/4"Weig	Ber length25cm25cmCall length reducting equipment334 cmSize10Labe dameter36 rm mLabe dameter355 kgWeight (ext) battery and outing equipment)355 kgWeight (ext) battery and outing equipment)355 kgWeight (ext) battery and outing equipment)355 kgENGNEHADC (2 brushed)EQUENCENTHADC (2 brushed)EQUENCENTHADC (2 brushed)Connected digital function et (cac).Hat and the cache and		
full engl nucluding equipment304 cmFull engl nucluding equipment35 framTabe length35 framTabe length35 fragWeight (ed. tathry and outing equipment)35 fragWeight (ed. tathry equipment)35 fragWeight (ed. tathry equipment)35 fragWeight (ed. tathry equipment)35 fragWeight (ed. tathry equipment)More pointMore pointPMDC (2 bushed)Chain typePMDC (2 bushed)Chain typeHOChain typeNatagana Common Service Tool: N/A N/APich1/4°Sproteit typeSproteit typeConnectivityNataganaCommon Service Tool: N/A N/APich1/4°Sproteit typeSproteit typeConnectivityNataganaCommon Service Tool: N/A N/ANate pack Paper materialGoldUbencomeSproteit typeConnectivityNataganaCommon Service Tool: N/A N/ANate pack Paper materialGoldUbencomeSproteit typeConnectivitySproteit typeConnectivitySproteit typeWast pack Paper materialGoldMater pack Paper materialGold <td< td=""><td>Full legit, including quiting equipment 304 cm Size 10 Tube dength 95 cm Tube dength 950 cm Weight (oct builting equipment) 355 kg Chart type PAUC (2 builted) Chart type Hugagara Common Service Tot) NA NA Pitch 1/4* Pitch 1/4* Sprocket type Spar Connected digital function set (calc) Natagara Common Service Tot) NA NA Pitch 1/4* Pitch 1/4* Sprocket type Spar Connected digital function set (calc) Natagara Common Service Tot NA NA UBRECANTS 0071 UBRECANTS 0071 UBRECANTS 0071 Daga Chapte material 00 Meatot total 0</td><td></td><td>· · · · · · · · · · · · · · · · · · ·</td></td<>	Full legit, including quiting equipment 304 cm Size 10 Tube dength 95 cm Tube dength 950 cm Weight (oct builting equipment) 355 kg Chart type PAUC (2 builted) Chart type Hugagara Common Service Tot) NA NA Pitch 1/4* Pitch 1/4* Sprocket type Spar Connected digital function set (calc) Natagara Common Service Tot) NA NA Pitch 1/4* Pitch 1/4* Sprocket type Spar Connected digital function set (calc) Natagara Common Service Tot NA NA UBRECANTS 0071 UBRECANTS 0071 UBRECANTS 0071 Daga Chapte material 00 Meatot total 0		· · · · · · · · · · · · · · · · · · ·
Size 10 Size 10 Tube denerfer 35 mm Tube inerger 395 kg Weight (excl clains explanment) Weight (excl clains explanment) Connected digital function set (calc) Huse area Common Service Tool. NA N/A Pich 1/4 Sprodel type Spar Connected digital function set (calc) Huse area Common Service Tool. NA N/A Pich 1/4 Pich 1/2	See 10 Deb diametric 35 mm Tube ingth 355 hq Weight (ext outing equipment) 355 hq Weight (ext outing equipment) 355 hq Weight (ext outing equipment) 355 hq ENGNE Moto type EQUIPMENT HOC (2 brushed) EQUIPMENT Husparae Common Service Tool H/A N/A Pitch 1/4* Sproket type Sport Connected digita function at (calc) Nit appleable UBRCONTS Nit appleable UBRCONTS Nit appleable MATERIAS 0 0 MATERIAS 0 0 MATERIAS 0 0 Materiad A 0 0 Paper material total		
Tube langh35 mmWeight (excl. battery and cutting equipment)355 kgWeight (excl. battery and cutting equipment)Weight (excl. battery and cutting equipment)Weight (excl. battery and cutting equipment)Weight (excl. battery and cutting equipment)Chant typeHODConnecteryHODConnecterySpartConnecterySpartConnecterySpartConnecteryNot tapplicableUBRACNATSUBRACNATSWeight (excl. battery and cutting equipment)0071Power struct typeOgMatter ack Paper material0gMatter ack Paper material0gMatter ack Paper material0gMatter ack Paper material123 gMatter ack Paper material123 gPaper material total123 gPaper material total5 gPaper material total2 gPaper material total12 gPaper material total5 gPaper material total5 gPaper material total5 gPaper material total6 gPaper material total100 mmPaper material total100 mmPaper material total100 mmPaper material total100 m	Tube Grand35 mmWeight (act bating acupment)355 kgWeight (act bating acupment)355 kgWeight (act bating acupment)355 kgBRNRPMC (2 brushed)Cometed digital function set (act bating acupment)PMC (2 brushed)Cometed digital function set (act bating acupment)Hussaran Common Service Tool (NA ACometed digital function set (act)PMC (2 brushed)Cometed digital function set (act)Hussaran Common Service Tool (NA APath1/4Sprocket typeSpurCometed digital function set (act)Nat bagitalianCometed digital function set (act bagitalianOg 1Cometed digital function set (act bagitalianOg 1Rest (act bagitalianOg 1Paper material balOg 1Cometed digitalianSg 1Cometed digitalianSg 1Cometed digitalianOg 1Paper material balOg 1Cometed digitalianSg 1Cometed digitalianSg 1Cometed digitalianSg 1Cometed digitalianSg 1 <td></td> <td></td>		
Tube length1900 mmWeight (excl. cuing equipment)355 kgWeight (excl. cuing equipment)355 kgWeight (excl. cuing equipment)355 kgWeight (excl. cuing equipment)355 kgWolt YapPMC (2 hushed)EQUENTNPMC (2 hushed)Cuina typeMOC (2 hushed)Connected digital function set (calc)Husgeara Common Service Tool N/A N/APichNageara Common Service Tool N/A N/APichSparlSproket TypeSparlConnected digital function set (calc)Nageara Common Service Tool N/A N/APichSproket TypeConnected digital function set (calc)Nageara Common Service Tool N/A N/APichSproket TypeConnected digital function set (calc)Nageara Common Service Tool N/A N/APichNageara Common Service Tool N/A N/AConnected digital function set (calc)Nageara Common Service Tool N/A N/APichNageara Common Service Tool N/A N/AConnected digital function set (calc)Nageara Common Service Tool N/A N/APichNageara Common Service Tool N/A N/APichNageara Common Service Tool N/A N/APichNageara Common Serv	Tube length1900 mmWeight (ext lengt equipment)355 kgWeight (ext lengt equipment)355 kgWeight (ext lengt equipment)355 kgWeight (ext lengt equipment)355 kgWeight (ext lengt equipment)MDC (2 brushed)EQUIPMENTHOOConnected digital function set (calc)Hoosyana Connon Service Tool IV/A N/APitch1/4Spraket topicSpraketConnected digital function set (calc)Not applicableUBRICANTSUBRICANTSUBRICANTS00/1Of tark volume00/1Power/fuel typeBattaryMaster pack Paper matarial0Master pack Paper matarial0Master pack Paper matarial0UPE (Calc) Load0Paper (FAP 22)1/25 gPaper (FAP 22)1/25 gPaper (FAP 22)0Paper (FAP 22)2Paper (FAP		
Weight (exic utting equipment)355 kgWeight (exic utting equipment)355 kgWeight (exic utting equipment)355 kgWeight (exic utting equipment)MCC (2 brushed)Roft rigeMCC (2 brushed)Chain typeHOOConnected digid function set (calc)Husgenra Common Service Tool : NA N/APath1/4°Sprodet typeSprodet typeConnected digid function set (calc)Not applicablePath1/4°Sprodet typeSprodet typeConnected digid function set (calc)Not applicableUBRACNTSNot applicableUBRACNTS0071Nater Pack Pape material0071Power Hust Sprodet type09Mater Pack Pape material09Metal total09Paper (MP 20)125 gPaper material total5 gPaper (AP 20)29Paper total5 gPaper total29Paper total5 gPaper total5 gPaper total5 gPaper total5 gPaper total7 gPaper total5 gPaper total7 gPaper total30 mnPaper total30 mnPaper total30 mnPackagng height1400 mn <td>Weight (act buttery and cutting exponent)355 kgENGINE355 kgENGINEPMC (2 butshed)More typePMC (2 butshed)EVUIPMENTHOOCharn typeHOOConnected digital function set (calc)Husseyana Common Service Tool: WANAPitch1/4*Spincleat typeSpurConnected digital function set (calc)Not applicableILUBRICANTSSpurConnected digital function set (calc)Not applicableUnable typeSpurConnected digital function set (calc)Not applicableILUBRICANTSSpurUBRICANTSSpurMaster pack: Paper material0071Power hold typeSpurMaster pack: Paper material0gMetter CollSpurPaper (MP 22)125 gPaper material total123 gUPE (0A) totalSpPaper (MP 22)2gPaster for totalSpPaster for</td> <td></td> <td></td>	Weight (act buttery and cutting exponent)355 kgENGINE355 kgENGINEPMC (2 butshed)More typePMC (2 butshed)EVUIPMENTHOOCharn typeHOOConnected digital function set (calc)Husseyana Common Service Tool: WANAPitch1/4*Spincleat typeSpurConnected digital function set (calc)Not applicableILUBRICANTSSpurConnected digital function set (calc)Not applicableUnable typeSpurConnected digital function set (calc)Not applicableILUBRICANTSSpurUBRICANTSSpurMaster pack: Paper material0071Power hold typeSpurMaster pack: Paper material0gMetter CollSpurPaper (MP 22)125 gPaper material total123 gUPE (0A) totalSpPaper (MP 22)2gPaster for totalSpPaster for		
Weight (exil cutting equipment)35 kgENGINEPMDC (2 brushed)EQUIPMENTPMDC (2 brushed)EQUIPMENTH00Connected digital function set (cale)H00Connected digital function set (cale)H00Pinta1/4"Strocket fugoSpurConnected digital function set (cale)H00Pinta1/4"Strocket fugoSpurConnected digital function set (cale)SpurPinta1/4"Strocket fugoSpurConnectivelySpurConnectivelySparConnectivelySparConnectivelySparConnectivelySparMatter pack-Pager materialSparMatter pack-Pager materialSparPaper Repar material totalSparLiPF (A4) foatSparLiPF (A4) foatSpar	Weight (scil cutting sequences)355 fig.ENINEPMDC (2 brushed)EQUENCEPMDC (2 brushed)EQUENCEHotoEQUENCEHotoConnected digital function set (calc)HotoPrich1/4"Spricket typeSourConnected digital function set (calc)Not applicableEUENICACTSSourConnected digital function set (calc)Not applicableLURICACTSSourConnected digital function set (calc)Not applicableLURICACTSOpAsser pack Paper material0071Rower/Lud TypeBatteryMATERIALSOpMatterial StateOpMatterial StateOpPaper (PAP 22)125 gPaper (PAP 22)125 gPaper (PAP 22)SigPaper (PAP 22)Sig <td< td=""><td></td><td></td></td<>		
ENGNunderspeedBornerBornerConsented outspeedBornerConsented outspeedBornerConsented outspeedBornerParted outspeedBornerStroke outspeedBornerConsented outspeedBornerStroke outspeedBornerConsented outspeed <td>Instrume Mode rype Moder type PMOC (2 brushed) Chart type HOD Chart type HOD Connected digital function set (calc) Husquara common Service Tool: N/A N/A Pitch LV4 Sprocket type Spart Connected digital function set (calc) Not applicable LUBRICANTS Spart Connected digital function set (calc) Not applicable UBRICANTS OO7 1 Connected digital function set (calc) Not applicable Ideat total OO7 1 Rest rest type Og 0 Mettal total Og 0 Deper (PAP 22) 125 g Pager material Og 0 Pager material total 172 g Deper (CAP 22) Spart Calci total Spart Calci total Pager material total Og 0 Pager function set (calc) Spart Calci total Pager function set (calc) Spart Calci total Pager function set (calc) Spart Calci total Pager function time (fine bactor) Spare Calci total <</td> <td>Weight (execution and change optimistry</td> <td></td>	Instrume Mode rype Moder type PMOC (2 brushed) Chart type HOD Chart type HOD Connected digital function set (calc) Husquara common Service Tool: N/A N/A Pitch LV4 Sprocket type Spart Connected digital function set (calc) Not applicable LUBRICANTS Spart Connected digital function set (calc) Not applicable UBRICANTS OO7 1 Connected digital function set (calc) Not applicable Ideat total OO7 1 Rest rest type Og 0 Mettal total Og 0 Deper (PAP 22) 125 g Pager material Og 0 Pager material total 172 g Deper (CAP 22) Spart Calci total Spart Calci total Pager material total Og 0 Pager function set (calc) Spart Calci total Pager function set (calc) Spart Calci total Pager function set (calc) Spart Calci total Pager function time (fine bactor) Spare Calci total <	Weight (execution and change optimistry	
Motor type PMDC (2 brushed) EQUIPMENT Ho0 Connected digital function set (calc) Husqnara Common Service Tool: N/A N/A Pitch 1/4* Sprocket type Spur Connected digital function set (calc) Not applicable Utark volume Spur Connectivity Not applicable Utark volume 0071 Power/Tool type Battery Ottark volume 0g Power/Tool type 0g Master pack: Paper material 0g Metal total 0g Paper (PAP 20) 125 g Paper material total 1723 g DEE (04) Iol 5 g HOPE (02) total 2g Paper full 2g Paper full 2g Paper full 2g Paper full 0g Paper full 2g Paper full 2g Paper full 7g Paper full 20 rmm Paper full 20 rmm Pa	Motor type PMOC (2 brushed) EQUIPMENT Hoto Connected digital function set (calc) Huspana Common Service Tod: IVANA Pitch 1/4* Sprocket type Spar Connectivity Net applicable UBRICANTS 0071 Off tank volume 0071 Power/tuel type Battery MATERIALS 09 Matter pack Paper material 09 Matter pack Paper material 09 Paper (PAP 22) 125 g Paper material total 1723 g LOPE (cold) for 5g PAPE (OP 20) 5g PAPE (OP 20) 5g PAPE (OP 10d) 5g PAPE (OP 10d) 5g PAPE (OP 10d) 5g PASID total 7g PSIDS/HES (OS) total 0g PASASID total 7g PSIDS/HES (OS) tota		0.00 kg
EQUIPMENTHomChain typeHomChancet digital function set (calc)Husquara Common Service Tod : NA NAPitchJardSprocket typeJardConnectidigital function set (calc)Mutaguara Common Service Tod : NA NAPitchJardSprocket typeSup andConnectidigital function set (calc)Mutaguara Common Service Tod : NA NAConnectidigital function set (calc)Mutaguara Common Service Tod : NA NAConnectidigital function set (calc)Mutaguara Common Service Tod : NA NAConnectidigital function set (calc)MutaguaraConnectidigital function set (calc)MutaguaraConnectidigital function set (calc)MutaguaraPost calc)MutaguaraMutag	FOURMENTModChain typeHusquran Common Service Tool: N/A N/APitch1/4°Sprocket typeSpurConnected dight function set (calc)Nut applicableConnected dight function set (calc)SpurConnected dight function set (calc)SpurMater and SpurSpurMater and SpurSpurMater and SpurSpurPaper (PAP 2)SpurPaper (PAP 2)SpurPaper (PAP 2)SpurPaper (PAP 2)SpurSpurSpurSpurSpurPaper (PAP 2)SpurPaper (PAP 2)SpurPaper (PAP 2)SpurSpurSpurSpurSpurPaper (PAP 2)SpurPaper (PAP 2)SpurPaper (PAP 2)SpurPaper (PAP 2)SpurPaper (PAP 2)		PMDC (2 brushed)
Chain type H00 Connected digital function set (calc) Husquana Common Service Tool: N/A N/A Pitch 1/4* Sprocket type Spur Connectivity Not applicable LobeRCANTS 0071 Off ank volume 0071 Power/buel type Battery MATERIAS 0 MATERIAS 0 Paper (PAP 22) 0 Paper (PAP 22) 125 g Paper (PAP 22) 125 g Paper (PAP 22) 125 g Paper (PAP 22) 122 g Paper (PAP 22) 123 g UDFE (04) fold 5 g Paper (PAP 22) total 0 g Paper (PAP 22) total 2 g Paper (PAP 22) total 2 g Paper (PAP 22) total 2 g Paper (PAP 22) total 0 g Paper (PAP 22) total 2 g Pastic fold total 3 g Pastic fold total 2 g Pastic fold total 2 g Pastic fold total 3 g	Chain type H00 Connected digita function set (calc) Husquema Common Service Tool: N/A N/A Ditch 1/4 Sprocket type Spur Connectivy Nat applicable UBRICANTS 0071 Oli tarik volume 0071 Rower/Diel Type Battery MATEMALS 0 MATEMALS 0 Matematicable 0 Paper material 0 UPF (0/2) total 0 DPF (0/2) total 0 Paper material 0 DPF (0/2) total 2 Pasic for Itotal 2 Pasic for Itotal 2 Pasic for Itotal 150 mm Pasicable 1400 mm Paskagning height 1400 mm <t< td=""><td></td><td>PMDC (2 brushed)</td></t<>		PMDC (2 brushed)
Connected digital function set (calc) Husquarma Common Service Tool: N/A N/A Pitch 1/4° Sprocket type Spur Connected digital function set (calc) Spur Connectively Nat applicable LUBRICANTS 0071 Ottank volume 0071 Rower / volut type Battery MATERIAS 0g Materiack Raper material 0g Materiack Raper material 0g Paper (PAP 22) 125 g Paper referial total 122 g LDPE (od) total 5 g POPE (02) total 0 q PET (01) total 5 g Plastic foid total 5 g Plastic total 5 g <	Connected digital function set (calc) Husparna Common Service Tool: N/A N/A Pritch 1/4" Sprocket type Sput Connectivity Nat applicable UBRICANTS 0071 Olt tank volume 0071 Prower / Nuel type Battery Matter pack: Paper material 0 Master pack: Paper material 0 Master pack: Paper material 0 Mater total 7.9 PROVE / Nuel Total 7.9 Paper (PAP 22) 125.9 Paper material total 1723.9 DPF (0.4) fold 5.9 PAPE (2.2) total 5.9 PAPE (2.2) total 2.9 Plastic foid total 5.9 PAPE (0.2) total 0.9 Paster foid total 5.9 Paster foid total 7.9 PS/FEPA/HPS (C6) total 7.9 PACKAGINK 1400 mm Pastaging length 1400 mm Pastaging width 2.30 mm Count by in Mastar pack 3.0 dm2		
Pich 1/4" Sprocket type Spur Connectivity Nataplicable LUBRICANTS 0071 Oll tank volume 0071 Power/Luel type Battery MATERNALS 0g Master pack Paper material 0g Master pack Paper material 0g Paper (PAP 22) 125 g Paper material total 122 g LDPE (04) foll 5 g HOPE (02) total 0g Paster fold total 2 g Paster fold total 5 g Plastic foil total 2 g Plastic foil total 2 g Plastic foil total 7 g Packaging height 150 mm Packaging volume 48.30 dm³ Packaging volume 48.30 dm³ Packaging volume 323 mm Quantry in Master pack 337.9 dB(A) Sound power level, quaranteed (UMA) 37.9 dB(A) Sound power level, quaranteed (UMA) 37.9 dB(A) Sound power level, quaranteed (UMA) 30.7 dB(A) Sound power level, quaranteed (UMA) 37.9 dB(A) <td>Prich 1/4* Sprocket type Spur Connectivity Net applicable UBRICANTS 001 Ol tark volume 0.0071 Power/Netl type Battery MATERNALS 0.0071 Master pack Paper material 0.0071 Master pack Paper material 0.00 Master pack Paper material 0.00 Paper (PAP 22) 125 g Paper material total 1723 g DPE (0.01 foll 5 g PDPE (0.02 total 0 g PET (0.1) total 2 g Pastor (right total 2 g Pastoright total 2 g<!--</td--><td></td><td></td></td>	Prich 1/4* Sprocket type Spur Connectivity Net applicable UBRICANTS 001 Ol tark volume 0.0071 Power/Netl type Battery MATERNALS 0.0071 Master pack Paper material 0.0071 Master pack Paper material 0.00 Master pack Paper material 0.00 Paper (PAP 22) 125 g Paper material total 1723 g DPE (0.01 foll 5 g PDPE (0.02 total 0 g PET (0.1) total 2 g Pastor (right total 2 g Pastoright total 2 g </td <td></td> <td></td>		
Sprocket type Spur Connectivity Not applicable Utark volume 0.071 Dil tank volume 0.071 Power / Uel type Battery Matter pack. Paper material 0 g Master pack. Paper material 0 g Metal total 0 g Paper (PAP 22) 125 g Paper material total 1723 g LDFE (0.4) foil 5 g HOPE (0.2) total 0 g Pastic foil total 5 g Pastic foil total 7 g Packaging height 1400 mm Packaging usidin 1400 mm Packaging volume 48.30 dm³ Packaging wolume 9379 dB(A) Sound power level, quaranteed (UMA) 97 dB(A) Sound power level, quaranteed (UMA) 97 dB(A)	Sprocket type Spur Connectivity Not applicable Ottark volume 0071 Power/fuel type Battery MatterNAS 09 Matter pack: Paper material 09 Master pack: Paper material 09 Master pack: Paper material 09 Paper (PAP 22) 125 g Paster (old total 2 g Paster (old total 7 g Paster (old total 7 g PackAging volume 48.3 00 m ³ <t< td=""><td></td><td></td></t<>		
Connectivity Not applicable LUBRICANTS 0/11 Oli tark volume 0/071 Power/Luel type Battery MATERIALS 0.9 Master pack Paper material 0.9 Master pack Paper material 0.9 Paper (PAP 22) 125 g Paper material total 1723 g LDFE (04) foll 5 g POPE (02) total 0 g PET (01) total 2 g Pastic foll total 5 g Paster foll total 5 g Pastic foll total 2 g Pastic foll total 5 g Pastic foll total 5 g Pastic foll total 5 g Pastic foll total 2 g Pastic foll total 2 g Pastic foll total 7 g Packaging height 150 mm Packaging notume 48.30 dm³ Packaging wolume 48.30 dm³ Packaging wolume 93.79 dR[A] Sound power level, waarateed (LWA) 93.79 dR[A] Sound power level, m	Connectivity Not applicable LUBRCANTS 0.071 Ditrark volume 0.071 Power/fuel type Battery MATERIALS 0g Matter pack: Paper material 0g Mater pack: Paper material 0g Mater pack: Paper material 0g Paper (RAP 22) 125 g Paper material total 1723 g LIPE (04) foil 5 g HOPE (02) total 0 g PET (01) total 2 g Pastic rigit total 2 g Plastic total 7 g PS/PS/HPK (S(6) total 0 g PACKAGING 1 Packaging height 1400 mm Packaging with 48.30 dm³ Packaging with 230 mm Packaging with 97 dB(A) Sound power level guaranteed (LWA) 97 dB(A) Sound power level guaranteed (LWA) 97 dB(A) Sound power level measured 93.79 dB(A) Sound power level measured 93.79 dB(A) Sound power level measured 93.79 dB(A) </td <td></td> <td></td>		
LUBRICANTS Image: Contract State	LUBRICANTSOD1Oil tark volume0071Power/luel typeBatteryMATERIALS0Master pack: Paper material0 gMeal total0 gPaper (PAP 22)125 gPaper material total1723 gLDPE (04) fold5 gHDPE (02) total0 gPET (01) total2 gPastic fold total5 gPastic fold total7 gPS/EPS/HPS (06) total0 gPACKAGING100 mmPackaging height150 mmPackaging withh1400 mmPackaging withh200 mmOuntify in Master pack1Sound power level, masured93.79 dB(A)Sound power level, masured93.79 dB(A)Sound power level, guarantee (UMA)97 dB(A)Sound power level, data total (Aver)1475 m/s²Daily Vibration (Acqv)1475 m/s²Daily Vibration (Acqv)3 hEquivalent vibration level (darv, equine thered, extended0.773 m/s²		
Oltark volume0.07 lPower/lul typeBatteryMATERIALS0gMatter pack. Paper material0gMatet pack. Paper material0gMatet pack. Paper material0gPaper (PAP 22)125 gPaper material total1723 gLDPE (04) foil5 gHDPE (02) total0gPastic rigid total2 gPastic rigid total5 gPastic rigid total7 gPastic rigid total7 gPackaging height9 gPackaging height100 mmPackaging volume48.30 dm³Packaging volume30 mmPackaging volume320 mmOutantty in Master pack320 mmSound power level, guaranteed (IWA)3379 dB(A)Sound power level, guaranteed (IWA)3379 dB(A)Sound pressure level at operators ear806 dB[A)Vibration (Aeqv)1475 m/s²Daily Vibration Exposure (A8)1475 m/s²	Olf Lank volume 0071 Power //vol type Battery MATERIALS 0g Master pack. Paper material 0g Metal total 0g Paper (PAP 22) 125 g Paper material total 1723 g LDPE (04) foil 5 g HDPE (02) total 0g Pastic foil total 5 g Pastic foil total 2 g Pastic foil total 7 g PS/EPS/HPS (06) total 0 g PACKABING 7 g Packaging height 150 mm Packaging length 1400 mm Packaging woldm 230 mm Quantity in Master pack 337 dB(A) Sound power level, quaranteed (WA) 37 dB(A) Sound power level, quarantee (WA) 37 dB(A) Sound power level, quaranteed (WA) <td>Connectivity</td> <td>Not applicable</td>	Connectivity	Not applicable
Power/fuel type Battery MATERNALS Image: Comparison of the system state type in material O g Master pack Paper material O g Gg Master pack Paper material O g Gg Paper (PAP 22) 125 g 127 g Paper material total 172 g 172 g DPE(04) fol 5 g 172 g DPE(04) fol 0 g 2 g Paster fol total 2 g 125 g Paster fol total 2 g <t< td=""><td>Power/fluel type Battery MATERIALS 0g Master pack-Raper material 0g Metal total 0g Paper (PAP 22) 125 g Paper material total 1723 g LDPE (O4) foil 5g HDFE (O2) total 0g PET (01) total 2g Pastic total total 5g Plot (D1) total 2g Pastic total total 7g PS/EPS/HIPS (O6) total 0g PAckaGing height 150 mm Packaging height 1400 mm Packaging height 1400 mm Packaging width 230 mm Quarter level quaranteed (LWA) 97 dB(A) Sound power level guaranteed (LWA) 379 dB(A) Sound power level quaranteed (LWA) 1475 m/s² Daily Vibration (Acou) 1475 m/s² Daily Vibration (Acou) 1475 m/s² Daily Vibration level (An eq.) rear handle 0773 m/s²</td><td>LUBRICANTS</td><td></td></t<>	Power/fluel type Battery MATERIALS 0g Master pack-Raper material 0g Metal total 0g Paper (PAP 22) 125 g Paper material total 1723 g LDPE (O4) foil 5g HDFE (O2) total 0g PET (01) total 2g Pastic total total 5g Plot (D1) total 2g Pastic total total 7g PS/EPS/HIPS (O6) total 0g PAckaGing height 150 mm Packaging height 1400 mm Packaging height 1400 mm Packaging width 230 mm Quarter level quaranteed (LWA) 97 dB(A) Sound power level guaranteed (LWA) 379 dB(A) Sound power level quaranteed (LWA) 1475 m/s ² Daily Vibration (Acou) 1475 m/s ² Daily Vibration (Acou) 1475 m/s ² Daily Vibration level (An eq.) rear handle 0773 m/s ²	LUBRICANTS	
MATERIALSOgMaster pack-Paper materialOgMetal totalOgPaper (PAP 22)125 gPaper material total1723 gDPE (04) total5 gHOPE (02) totalOgPET (01) total2 gPlastic foil total2 gPlastic foil total2 gPlastic foil total7 gPackAging height7 gPackaging height150 mmPackaging height160 mmPackaging volume48.30 dm³Packaging volume30 mmQuantity in Master pack30 mmSound power level, measured (LWA)9.379 dB(A)Sound power level, at operators ear80.6 dB(A)VIBARTONS1475 m/s²Daly Vibration (Aeqv)1475 m/s²Daly Vibration Exposure (A8)1475 m/s²	MATERIALSImage: Constraint of the second	Oil tank volume	0.071
Master pack Paper material 0 g Metal total 0 g Paper (PAP 22) 125 g Paper material total 1723 g LDPE (04) toil 5 g HDPE (02) total 0 g PET (01) total 2 g Plastic foil total 5 g Plastic foil total 2 g Plastic total 7 g PS/FES/HIPS (06) total 0 g PACKAGING 7 g Packaging height 1400 mm Packaging height 1400 mm Packaging neight 1400 mm Packaging with 2 30 mm Packaging with 9 7 dB(A) Sound power level, guaranteed (LWA) 9 7 dB(A) Sound power level, guaranteed (LWA) 9 379 dB(A) Sound power level at operators ear 9 379 dB(A) Sound power level at operators ear 9 379 dB(A) Sound power level at operators ear </td <td>Master pack Paper material 0.g Metal total 0.g Paper (PAP 22) 125 g Paper (PAP 22) 1723 g IDPE (02) total 0.g PAPET (PAP 22) 0.g Paper (PAP 22) 0.g IDPE (02) total 0.g PET (01) total 2.g Plastic rigid total 2.g Plastic rigid total 2.g Plastic rigid total 2.g Pastic rigid total 2.g Pack Asing height 7.g PackAsing length 150 mm Packasing use pack 230 dm³ Packaging use pack 230 mm Quantity in Master pack 1 Sound power level quaranteed (LWA) 97 dB(A) Sound power level quaranteed (LWA) 97 dB(A) Sound power level quaranteed (LWA) 1475 m/s² Daily Vibration (Acqv) 1475 m/s² Daily Vibration (Acqv) 1475 m/s² Daily Vibration Inevel(av eq) rear nandle 073 m/s² Daily Vibration Inevel(av eq) rear nande 073 m/s²</td> <td>Power/fuel type</td> <td>Battery</td>	Master pack Paper material 0.g Metal total 0.g Paper (PAP 22) 125 g Paper (PAP 22) 1723 g IDPE (02) total 0.g PAPET (PAP 22) 0.g Paper (PAP 22) 0.g IDPE (02) total 0.g PET (01) total 2.g Plastic rigid total 2.g Plastic rigid total 2.g Plastic rigid total 2.g Pastic rigid total 2.g Pack Asing height 7.g PackAsing length 150 mm Packasing use pack 230 dm³ Packaging use pack 230 mm Quantity in Master pack 1 Sound power level quaranteed (LWA) 97 dB(A) Sound power level quaranteed (LWA) 97 dB(A) Sound power level quaranteed (LWA) 1475 m/s² Daily Vibration (Acqv) 1475 m/s² Daily Vibration (Acqv) 1475 m/s² Daily Vibration Inevel(av eq) rear nandle 073 m/s² Daily Vibration Inevel(av eq) rear nande 073 m/s²	Power/fuel type	Battery
Metal total0 gPaper (PAP 22)125 gPaper material total125 gPaper material total5 gLDPE (04) foil5 gHDPE (02) total0 gPET (01) total2 gPlastic rigid total2 gPlastic rigid total2 gPlastic rigid total7 gPS/FE/HIPS (05) total0 gPACKAGING150 mmPackaging height150 mmPackaging woltme48.30 dm³Packaging woltme30 mmPackaging woltme30 mmPackaging woltme30 mmSound power level guaranteed (LWA)97 dB(A)Sound power level quaranteed (LWA)93.79 dB(A)Sound power level measured33.79 dB(A)Sound power level measured33.79 dB(A)Sound power level measured1475 m/s²Daily Vibration (Aeqv)1475 m/s²Daily Vibration Exposure (A8)1475 m/s²	Metal total 0 g Paper (PAP 22) 125 g Paper material total 1723 g LDFE (04) foil 5 g HDPE (02) total 0 g PET (01) total 2 g Plastic foil total 5 g Plastic foil total 2 g Plastic foil total 7 g Pester total 7 g Ps/EPS/HIPS (06) total 0 g Packaging height 150 mm Packaging use 48.30 dm³ Packaging with 200 mm Output in Master pack 11 Sound power level guaranteed (LWA) 93 79 dB(A) Sound power level areagured 93 79 dB(A) Sound power level areagured 80 6 dB(A) VIBRATIONS 1475 m/s² Daily Vibration Exposure (A8) 1475 m/s² Daily Vibration Exposure (A8) 1475 m/s² Daily Vibration Exposure (A8) 073 m/s² Equivalent Vibration level (abv. eq) rear handle 0773 m/s² Equivalent Vibration level (abv. eq) rear handle 0773 m/s²	MATERIALS	
Metal total0 gPaper (PAP 22)125 gPaper material total125 gPaper material total5 gLDPE (04) foil5 gHDPE (02) total0 gPET (01) total2 gPlastic rigid total2 gPlastic rigid total2 gPlastic rigid total7 gPS/FE/HIPS (05) total0 gPACKAGING150 mmPackaging height150 mmPackaging woltme48.30 dm³Packaging woltme30 mmPackaging woltme30 mmPackaging woltme30 mmSound power level guaranteed (LWA)97 dB(A)Sound power level quaranteed (LWA)93.79 dB(A)Sound power level measured33.79 dB(A)Sound power level measured33.79 dB(A)Sound power level measured1475 m/s²Daily Vibration (Aeqv)1475 m/s²Daily Vibration Exposure (A8)1475 m/s²	Metal total 0 g Paper (PAP 22) 125 g Paper material total 1723 g LDFE (04) foil 5 g HDPE (02) total 0 g PET (01) total 2 g Plastic foil total 5 g Plastic foil total 2 g Plastic foil total 7 g Pester total 7 g Ps/EPS/HIPS (06) total 0 g Packaging height 150 mm Packaging use 48.30 dm³ Packaging with 200 mm Output in Master pack 11 Sound power level guaranteed (LWA) 93 79 dB(A) Sound power level areagured 93 79 dB(A) Sound power level areagured 80 6 dB(A) VIBRATIONS 1475 m/s² Daily Vibration Exposure (A8) 1475 m/s² Daily Vibration Exposure (A8) 1475 m/s² Daily Vibration Exposure (A8) 073 m/s² Equivalent Vibration level (abv. eq) rear handle 0773 m/s² Equivalent Vibration level (abv. eq) rear handle 0773 m/s²	Master pack-Paper material	0 g
Paper (PAP 22)125 gPaper material total1723 gPaper material total1723 gLDPE (04) foil5 gLDPE (02) total0 gPET (01) total2 gPlastic foil total5 gPlastic foil total2 gPlastic foil total7 gPastic foil total7 gPS/EPS/HIPS (06) total0 gPAckaging height150 mmPackaging user1400 mmPackaging user230 mmPackaging user pack230 mmQuantity in Master pack30 dm³SUND ADN OSE97 dB(A)Sound power level, guaranted (LWA)93 79 dB(A)Sound power level, guaranted (LWA)30 dm3Sound power level at operators ear4475 m/s²Daily Vibration (Aeqy)1475 m/s²Daily Vibration Exposure (A8)1475 m/s²	Paper (PAP 22) 125 g Paper material total 1723 g LDPE (04) fold 5 g HDPE (02) total 0 g PET (01) total 2 g Plastic rigit total 5 g Plastic rigit total 2 g Plastic rigit total 7 g PS/EPS/HIPS (06) total 0 g PACKAGING 0 Packaging pleight 150 mm Packaging volume 48.30 dm³ Packaging width 230 mm Quantity in Master pack 1 Sound power level guaranteed (LWA) 97 dB(A) Sound power level aperators ear 80.6 dB(A) Vibration (Aeqv) 1.475 m/s² Daily Vibration Exposure (AB) 1.475 m/s² Daily Vibration Nevel (abx, eq), front handle, collapsed 0.773 m/s² Equivalent vibration level (abx, eq), rear handle 0.773 m/s² Equivalent vibration level (aby, eq), rear handle 0.773 m/s²		
Paper material total 1723 g LDPE (04) foil 5 g HDPE (02) total 0 g PET (01) total 2 g Plastic foil total 5 g Plastic totil total 2 g Plastic total 7 g Plastic total 7 g PS/EPS/HIPS (06) total 0 g PACKAGING	Paper material total 1723 g LDPE (Q4) foil 5g IDPE (Q2) total 0g PET (Q1) total 2g Plastic foil total 5g Plastic foil total 2g Plastic foil total 7g PSEPS/HPS (06) total 0g PAcKAGING 0g PAcKaGING 0g Packaging height 150 mm Packaging length 1400 mm Packaging wolume 43.30 dm³ Packaging wolume 23.00 mm Quantity in Master pack 1 SOUND AND NOISE 30.00 mm Sound power level guaranteed (LWA) 97 dB(A) Sound power level aperators ear 80.6 dB(A) VIBRATIONS 1.475 m/s² Daily Vibration (Aeqy) 1.475 m/s² Daily Vibration (Aeqy) 3.h Equivalent vibration level (ahv eq) (rent handle, collapsed 0.773 m/s² Equivalent vibration level (ahv, eq), rent handle, extended 0.773 m/s²		
LDPE (04) foil 5 g HDPE (02) total 0 g PET (01) total 2 g Plastic foil total 5 g Plastic foil total 2 g Plastic foil total 0 g PS/EPS/HIPS (06) total 0 g Packaging height 150 mm Packaging height 150 mm Packaging wolume 48.30 dm³ Packaging wolume 230 mm Quantity in Master pack 1 Sound power level, guaranteed (LWA) 97 dB(A) Sound power level, measured 93.79 dB(A) Sound power level, measured 93.79 dB(A) Sound power level, measured 80(A) Sound power level, measured (LWA) 97 dB(A) Sound power level, measured 93.79 dB(A) Sound power level, measured <	LDPE (04) foll 5 g HDPE (02) total 0 g PET (01) total 2 g Plastic foil total 5 g Plastic foil total 2 g Plastic foil total 2 g Plastic foil total 2 g Plastic foil total 0 g PACKAGING 0 g Packaging length 150 mm Packaging volume 48.30 dm³ Packaging volume 48.30 dm³ Packaging width 230 mm Quantity in Master pack 1 Sound power level, guaranteed (LWA) 97 dB(A) Sound power level, guaranteed (LWA) 93.79 dB(A) Sound power level, guaranteed (LWA) 1475 m/s² Daily Vibration Exposure (A8) 1475 m/s² Daily Vibration Exposure (A8) 1475 m/s² Daily Vibration Time (Time factor) 3h Equivalent vibration level (ahv. eq), front handle, collapsed 0773 m/s² Equivalent vibration level (ahv. eq), rear handle 0.773 m/s²		
HDPE (02) total0 gPET (01) total2 gPlastic foil total5 gPlastic foil total2 gPlastic rigid total2 gPlastic rigid total7 gPlastic rigid total0 gPS/EPS/HIPS (06) total0 gPACKAGING-Packaging height160 mmPackaging volume48.30 dm³Packaging wolth230 mmPackaging wolth230 mmQuantity in Master pack1Sound power level, guaranteed (LWA)30.37 dB(A)Sound pressure level at operators ear30.6 dB(A)Vilbration KepoylMacMandemandemandemandemandemandemandemandem	HDPE (02) total 0 g PET (01) total 2 g Plastic foil total 5 g Plastic foil total 2 g Plastic foil total 2 g Plastic foil total 2 g Plastic foil total 7 g Pastic foil total 7 g PS/EPS/HPS (06) total 0 g PACKAGING 0 g Packaging height 150 mm Packaging length 1400 mm Packaging width 230 mm Quantity in Master pack 1 Sound ANN NOISE 1 Sound power level, guaranteed (LWA) 97 dB(A) Sound power level at operators ear 80 dB(A) VIBRATIONS 1 Daily Vibration (Aeqv) 1475 m/s² Daily Vibration Exposure (k8) 1475 m/s² Daily Vibration Exposure (k8) 1475 m/s² Daily Vibration Exposure (k8) 0793 m/s² Daily Vibration Exposure (k8) 0793 m/s² Daily Vibration Exposure (k8) 0793 m/s² Daily Vibration Nevel (Anv, eq) rear handle 0773 m/s² <td></td> <td></td>		
PET (01) total 2 g Plastic foil total 5 g Plastic foil total 2 g Plastic total 7 g PS/EPS/HIPS (06) total 0 g PACKAGING	PET (01) total 2 9 Plastic foli total 5 9 Plastic foli total 2 9 Plastic foli total 7 9 Plastic total 7 9 PS/EPS/HIPS (06) total 0 9 PACKAGING 150 mm Packaging height 1400 mm Packaging volume 48.30 dm³ Packaging volume 230 mm Quantly in Master pack 1 Sound power level guaranteed (LWA) 97 dB(A) Sound power level at operators ear 80.6 dB(A) VIBRATIONS 93.79 dB(A) Daily Vibration (Acqv) 1.475 m/s² Daily Vibration Exposure (A8) 1.475 m/s² Daily Vibration Exposure (A8) 0.773 m/s² Equivalent vibration level (Aiv, eq) rear handle, extended 0.773 m/s²		
Plastic foil total5 gPlastic rigid total2 gPlastic rigid total2 gPlastic total7 gPS/EPS/HIPS (06) total0 gPACKAGING150 mmPackaging height150 mmPackaging length1400 mmPackaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1Sound power level, guaranteed (LWA)97 dB(A)Sound power level, guaranteed (LWA)93.79 dB(A)Sound pressure level at operators ear806 dB(A)VIBRATIONS1Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	Plastic foil total 5 g Plastic rigid total 2 g Plastic rigid total 7 g PS/EPS/HIPS (O6) total 0 g PACKAGING		
Plastic rigid total2 gPlastic total7 gPS/EPS/HIPS (06) total0 gPACKAGING0Packaging height150 mmPackaging length1400 mmPackaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1SOUND AND NOISE97 dB(A)Sound power level, guaranteed (LWA)93.79 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1Daily Vibration (Aeqv)1475 m/s²Daily Vibration Exposure (A8)1475 m/s²	Plastic rigid total 2 g Plastic total 7 g PS/EPS/HIPS (06) total 0 g PACKAGING 0 Packaging height 150 mm Packaging uptime 48.30 dm³ Packaging wolume 48.30 dm³ Packaging width 230 mm Quantity in Master pack 1 SOUND AND NOISE 97 dB(A) Sound power level, guaranteed (LWA) 97 dB(A) Sound pressure level at operators ear 80.6 dB(A) VIBRATIONS 1 Daily Vibration (Aeqv) 1.475 m/s² Daily Vibration Exposure (A8) 1.475 m/s² Daily Vibration Inevel(ahv. eq), rear handle, collapsed 0.773 m/s² Equivalent vibration level(ahv. eq), rear handle, extended 0.773 m/s²		
Plastic total7 gPS/EPS/HIPS (06) total0 gPACKAGING0 gPackaging height150 mmPackaging length1400 mmPackaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1SOUND AND NOISE97 dB(A)Sound power level, guaranteed (LWA)97 dB(A)Sound pressure level at operators ear806 dB(A)VIBRATIONS1Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	Plastic total 7 g PS/EPS/HIPS (06) total 0 g PACKAGING		
PS/EPS/HIPS (06) totalO gPACKAGINGImage: constraint of the systemPackaging height150 mmPackaging length1400 mmPackaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1SOUND AND NOISE1Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	PS/EPS/HIPS (06) total 0 g Packaging height 150 mm Packaging height 1400 mm Packaging volume 48.30 dm³ Packaging width 230 mm Quantity in Master pack 1 Sound Dower level, guaranteed (LWA) 97 dB(A) Sound power level, guaranteed (LWA) 97.7 dB(A) Sound power level at operators ear 80.6 dB(A) ViBRATIONS 1 Daily Vibration (Aeqv) 1.475 m/s² Daily Vibration Exposure (A8) 1.475 m/s² Daily Vibration Time (Time factor) 3 h Equivalent vibration level. (ahv, eq) rear handle 0.773 m/s² Equivalent vibration level. (ahv, eq), rear handle, extended 0.773 m/s²		•
PACKAGINGIPackaging height150 mmPackaging length1400 mmPackaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1SOUND AND NOISE97 dB(A)Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	PACKAGING150 mmPackaging height150 mmPackaging length1400 mmPackaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1SOUND AND NOISE5Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound power level at operators ear80.6 dB(A)VIBRATIONS14.75 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Time (Time factor)3 hEquivalent vibration level, (ahv. eq), front handle, collapsed0.773 m/s²Equivalent vibration level (ahv. eq), rear handle0.773 m/s²Equivalent vibration level, (ahv. eq), rear handle, extended0.773 m/s²		
Packaging height150 mmPackaging length1400 mmPackaging volume48.30 dm3Packaging width230 mmQuantity in Master pack1SOUND AND NOISE97 dB(A)Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	Packaging height150 mmPackaging length1400 mmPackaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1SOUND AND NOISE1Sound power level, guaranteed (LWA)97 dB(A)Sound power level, guaranteed (LWA)97 dB(A)Sound power level at operators ear93.79 dB(A)Sound power level at operators ear80.6 dB(A)VIBRATIONS1.475 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²Daily Vibration Time (Time factor)3 hEquivalent vibration level (ahv, eq), rear handle, collapsed0.773 m/s²Equivalent vibration level (ahv, eq), rear handle, extended0.773 m/s²		~
Packaging length1400 mmPackaging volume48.30 dm³Packaging volume230 mmPackaging width230 mmQuantity in Master pack1SOUND AND NOISE97 dB(A)Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	Packaging length1400 mmPackaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1SOUND AND NOISE1Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1.475 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)3.hEquivalent vibration level (ahv, eq), front handle, collapsed0.773 m/s²Equivalent vibration level (ahv, eq), rear handle, extended0.773 m/s²		150 mm
Packaging volume48.30 dm³Packaging volume230 mmPackaging width230 mmQuantity in Master pack1SOUND AND NOISE97 dB(A)Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1.475 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	Packaging volume48.30 dm³Packaging width230 mmQuantity in Master pack1SOUND AND NOISE1Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Time (Time factor)3 hEquivalent vibration level (ahv, eq), front handle, collapsed0.773 m/s²Equivalent vibration level (ahv, eq), rear handle0.773 m/s²		
Packaging width230 mmQuantity in Master pack1SOUND AND NOISE97 dB(A)Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1.475 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	Packaging width230 mmQuantity in Master pack1SOUND AND NOISE97 dB(A)Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1.475 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Time (Time factor)3 hEquivalent vibration level (ahv, eq), rear handle, collapsed0.773 m/s²Equivalent vibration level (ahv, eq), rear handle, extended0.773 m/s²		
Quantity in Master pack 1 SOUND AND NOISE 97 dB(A) Sound power level, guaranteed (LWA) 97 dB(A) Sound power level, measured 93.79 dB(A) Sound pressure level at operators ear 80.6 dB(A) VIBRATIONS 91 Daily Vibration (Aeqv) 1.475 m/s ² Daily Vibration Exposure (A8) 1.475 m/s ²	Quantity in Master pack 1 SOUND AND NOISE 97 dB(A) Sound power level, guaranteed (LWA) 97 dB(A) Sound power level, measured 93.79 dB(A) Sound pressure level at operators ear 80.6 dB(A) VIBRATIONS 1.475 m/s² Daily Vibration (Aeqv) 1.475 m/s² Daily Vibration Exposure (A8) 1.475 m/s² Daily Vibration Time (Time factor) 3 h Equivalent vibration level (ahv. eq), front handle, collapsed 0.793 m/s² Equivalent vibration level (ahv. eq), rear handle 0.773 m/s²		
SOUND AND NOISEPSound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1.475 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	SOUND AND NOISESound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1.475 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²Daily Vibration Time (Time factor)3 hEquivalent vibration level (ahv. eq) rear handle0.793 m/s²Equivalent vibration level (ahv. eq), rear handle, extended0.773 m/s²		
Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONS1.475 m/s²Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²	Sound power level, guaranteed (LWA)97 dB(A)Sound power level, measured93.79 dB(A)Sound pressure level at operators ear80.6 dB(A)VIBRATIONSDaily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²Daily Vibration Time (Time factor)3 hEquivalent vibration level (ahv. eq), rear handle0.793 m/s²Equivalent vibration level (ahv. eq), rear handle, extended0.773 m/s²		-
Sound power level, measured 93.79 dB(A) Sound pressure level at operators ear 80.6 dB(A) VIBRATIONS 1.475 m/s ² Daily Vibration (Aeqv) 1.475 m/s ² Daily Vibration Exposure (A8) 1.475 m/s ²	Sound power level, measured 93.79 dB(A) Sound pressure level at operators ear 80.6 dB(A) VIBRATIONS 1.475 m/s² Daily Vibration (Aeqv) 1.475 m/s² Daily Vibration Exposure (A8) 1.475 m/s² Daily Vibration Time (Time factor) 3 h Equivalent vibration level (ahv, eq), front handle, collapsed 0.793 m/s² Equivalent vibration level (ahv, eq), rear handle 0.773 m/s²		
Sound pressure level at operators ear 80.6 dB(Å) VIBRATIONS 1 Daily Vibration (Aeqv) 1.475 m/s² Daily Vibration Exposure (A8) 1.475 m/s²	Sound pressure level at operators ear 80.6 dB(Å) VIBRATIONS 1.475 m/s² Daily Vibration (Aeqv) 1.475 m/s² Daily Vibration Exposure (A8) 1.475 m/s² Daily Vibration Time (Time factor) 3 h Equivalent vibration level (ahv. eq), front handle, collapsed 0.793 m/s² Equivalent vibration level (ahv. eq), rear handle 0.773 m/s² Equivalent vibration level (ahv. eq), rear handle, extended 0.773 m/s²		
VIBRATIONS Image: Constraint of the system Daily Vibration (Aeqv) 1.475 m/s ² Daily Vibration Exposure (A8) 1.475 m/s ²	VIBRATIONS 1.475 m/s² Daily Vibration (Aeqv) 1.475 m/s² Daily Vibration Exposure (A8) 1.475 m/s² Daily Vibration Time (Time factor) 3 h Equivalent vibration level (ahv. eq), front handle, collapsed 0.793 m/s² Equivalent vibration level (ahv. eq) rear handle 0.773 m/s² Equivalent vibration level (ahv, eq), rear handle, extended 0.773 m/s²		
Daily Vibration (Aeqv) 1.475 m/s ² Daily Vibration Exposure (A8) 1.475 m/s ²	Daily Vibration (Aeqv)1.475 m/s²Daily Vibration Exposure (A8)1.475 m/s²Daily Vibration Time (Time factor)3 hEquivalent vibration level (ahv. eq), front handle, collapsed0.793 m/s²Equivalent vibration level (ahv. eq) rear handle0.773 m/s²Equivalent vibration level (ahv. eq), rear handle, extended0.773 m/s²		00.0 uD(A)
Daily Vibration Exposure (A8) 1.475 m/s ²	Daily Vibration Exposure (A8) 1.475 m/s² Daily Vibration Time (Time factor) 3 h Equivalent vibration level (ahv. eq), front handle, collapsed 0.793 m/s² Equivalent vibration level (ahv. eq) rear handle 0.773 m/s² Equivalent vibration level (ahv. eq), rear handle, extended 0.773 m/s²		
	Daily Vibration Time (Time factor) 3 h Equivalent vibration level (ahv. eq), front handle, collapsed 0.793 m/s ² Equivalent vibration level (ahv. eq) rear handle 0.773 m/s ² Equivalent vibration level (ahv. eq), rear handle, extended 0.773 m/s ²		
Daily Vibration Time (Time factor) 3h	Equivalent vibration level (ahv. eq), front handle, collapsed 0.793 m/s² Equivalent vibration level (ahv. eq) rear handle 0.773 m/s² Equivalent vibration level (ahv. eq), rear handle, extended 0.773 m/s²		
	Equivalent vibration level (ahv. eq) rear handle 0.773 m/s ² Equivalent vibration level (ahv. eq), rear handle, extended 0.773 m/s ²		
	Equivalent vibration level (ahv, eq), rear handle, extended 0.773 m/s ²		
	Vibrations handlebar 1.475 m/s ²	Vibrations handlebar	1.475 m/s ²

ACCESSORIES





HUSQVARNA POLE SAW BLI20 BATTERY ATTACHMENT - BATTERY SERIES PK4 967 09 17-01 529 35 19-01



PROTECTIVE GLASSES - SUN X 544 96 37-03



 $\begin{array}{l} \mathsf{PROTECTIVE BOOTS} - (\mathsf{LEATHER}) \text{ WITH SAW} \\ \mathsf{PROTECTION} \ \mathsf{C20} \ \mathsf{SIZE} - \mathsf{EU} \ \mathsf{41}, \mathsf{AU/NZ} \ \mathsf{7.5} \\ \mathbf{597} \ \mathbf{65} \ \mathbf{94-41} \end{array}$



BLI10 BATTERY

967 09 16-01

 $\begin{array}{l} {\sf PROTECTIVE BOOTS-(LEATHER) WITH SAW} \\ {\sf PROTECTION C20 SIZE-EU 42, AU/NZ 8} \\ {\sf 597 65 94-42} \end{array}$



 $\begin{array}{l} \mathsf{PROTECTIVE BOOTS-(LEATHER) WITH SAW} \\ \mathsf{PROTECTION C20 SIZE-EU 45, AU/NZ 10.5} \\ \mathbf{597 65 94-45} \end{array}$



 $\begin{array}{l} \mathsf{PROTECTIVE BOOTS} \ \text{-} (\mathsf{LEATHER}) \ \mathsf{WITH} \ \mathsf{SAW} \\ \mathsf{PROTECTION} \ \mathsf{C20} \ \mathsf{SIZE} \ \text{-} \ \mathsf{EU} \ \mathsf{46}, \ \mathsf{AU/NZ} \ \mathsf{11} \\ \mathbf{597} \ \mathbf{65} \ \mathbf{94} \textbf{-} \textbf{46} \end{array}$



QC250 BATTERY CHARGER 967 97 01-05



BATTERY BAG 585 37 18-01



 $\begin{array}{l} \mathsf{PROTECTIVE BOOTS-(LEATHER) WITH SAW} \\ \mathsf{PROTECTION} \ \mathsf{C20} \ \mathsf{SIZE-EU} \ \mathsf{39, AU/NZ} \ \mathsf{5.5} \\ \mathbf{597} \ \mathbf{65} \ \mathbf{94-39} \end{array}$



 $\begin{array}{l} {\sf PROTECTIVE BOOTS-(LEATHER) WITH SAW} \\ {\sf PROTECTION C20 SIZE-EU 43, AU/NZ 9} \\ {\sf 597 65 94-43} \end{array}$



 $\begin{array}{l} \mbox{PROTECTIVE BOOTS - (LEATHER) WITH SAW} \\ \mbox{PROTECTION C20 SIZE - EU 47, AU/NZ 12} \\ \mbox{597 65 94-47} \end{array}$



 $\begin{array}{l} \mathsf{PROTECTIVE BOOTS-(LEATHER) WITH SAW} \\ \mathsf{PROTECTION C20 SIZE-EU 40, AU/NZ 6.5} \\ \mathbf{597 65 94-40} \end{array}$



 $\begin{array}{l} \mathsf{PROTECTIVE BOOTS-(LEATHER) WITH SAW} \\ \mathsf{PROTECTION C20 SIZE-EU 44, AU/NZ 9.5} \\ \mathbf{597 65 94-44} \end{array}$



HUSQVARNA HEDGE TRIMMER ATTACHMENT - BATTERY SERIES HK4 529 35 19-02



PROTECTIVE GLASSES - CLEAR X 544 96 37-01